Lovibond[®] Water Testing

Tintometer® Group



Reviewed on 01/23/2019

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 01/23/2019

1 Identification

- · Product identifier
- Trade name: Ammonium Molybdate Solution (Silica method 1)
- · Catalogue number: 46024, 460241
- · Application of the substance / the mixture: Reagent for water analysis

Manufacturer/Supplier: Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany

· Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

· Classification of the substance or mixture



Met. Corr.1 H290 May be corrosive to metals.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



Signal word Warning
 Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P390 Absorb spillage to prevent material damage.

· Other hazards No further relevant information available.

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

(Contd. of page 1)

3 Com	nosition/	informatio	n on ind	redients
	position	mornauc		n culonto

- Chemical characterization: Mixtures
- · Description: sulfuric acid solution
- · Composition and Information on Ingredients:
- Cancer Status IARC: Strong inorganic acid mists containing sulphuric acid can cause cancer.
- Percent ranges are used due to the confidential product information.

-			
CAS: 7664-93-9	sulphuric acid	Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	10–<15%
EINECS: 231-639-5		• · · · · · · · · · · · ·	
Index number: 016-020-00-8			
RTECS: WS5600000			

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- Immediately rinse with plenty of water. If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes (at least 15 min) under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink 1-2 glasses of water.

- If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed
- irritations

after inhalation: mucosal irritations, cough, breathing difficulty

after swallowing:

sickness

vomiting

diarrhoea

damage to the affected mucous membranes possible

· Danger:

Danger of circulatory collapse.

Danger of pulmonary edema.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

- Sulfur oxides (SOx)
- Nitrogen oxides (NOx)
- · Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

- Wear fully protective suit.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Ambient fire may liberate hazardous vapours.

(Contd. on page 3)

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

(Contd. of page 2)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Advice for non-emergency personnel: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
 Advice for emergency responders: Protective equipment: see section 8
 Environmental precautions: Do not allow product to reach sewage system or any water course.
 Methods and material for containment and cleaning up: Ensure adequate ventilation.
 - Use neutralizing agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

- Dispose contaminated material as waste according to item 13.
- **Reference to other sections** See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

• Precautions for safe handling

- · Advice on safe handling:
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Hygiene measures:

Avoid contact with the skin. Avoid contact with the eyes.

Take off immediately all contaminated clothing. Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:
- Store away from metals.

Do not store together with alkalis (caustic solutions).

- Store away from reducing agents.
- Further information about storage conditions:
- Protect from heat and direct sunlight.
- Protect from exposure to the light.
- Protect from humidity and water.
- · Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 7664-93	3-9 sulphuric acid
PEL (USA)	Long-term value: 1 mg/m ³
REL (USA)	Long-term value: 1 mg/m³
	Long-term value: 0.2* mg/m³ *as thoracic fraction
EL (Canada)	Long-term value: 0.2 mg/m³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.2 mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

· Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

· Personal protective equipment:

- · Breathing equipment: Use respiratory protective device against the effects of fumes/dust/aerosol.
- Recommended filter device for short term use: Filter P2
- · Protection of hands: Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

- · Material of gloves
- Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

· Penetration time of glove material

Value for the permeation: Level \leq 1 (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment: Do not allow product to reach sewage system or any water course.

9 Physical and chemical properties

· Appearance:	emical properties	
Form / Physical state: Color:	Fluid Colorless	
· Odor: · Odor threshold:	Odorless Not applicable.	
· pH-value at 20°C (68°F):	<2 Acidic	
 Melting point/freezing point: Initial boiling point and boiling range: 	Not determined. Not determined.	
· Flash point:	Not applicable.	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not self-igniting.	
 Danger of explosion: Flammability or explosive limits: 	Product does not present an explosion hazard.	
Lower: Upper:	Not applicable. Not applicable.	
· Oxidizing properties:	CAS 7664-93-9 : Oxidizing potential	
 Vapor Pressure: Density at 20°C (68°F): Relative density: Vapor density: Evaporation rate: 	Not determined. ~1.1 g/cm ³ (~9.18 lbs/gal) Not determined. Not determined. Not determined.	
· Solubility(ies) Water:	Fully miscible.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:	Not determined.	
 Solvent content: Organic solvents: Water: Solids content: 	0 % 86.9 % 2.8 %	

(Contd. of page 3)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

Other information

No further relevant information available

10 Stability and reactivity

· Reactivity see section "Possibility of hazardous reactions"

· Chemical stability Stable at ambient temperature (room temperature).

Possibility of hazardous reactions

Corrosive action on metals.

Reacts with metals forming hydrogen (Danger of explosion!)

Heating occurs when water is added.

Reacts with reducing agents.

Reacts with oxidizing agents. Reacts with acids and alkali (lyes).

Reacts with ammonia (NH₃).

· Conditions to avoid To avoid thermal decomposition do not overheat.

· Incompatible materials: metals combustible materials

organic solvents

Hazardous decomposition products: see section 5

1 Toxicological information

· Information on toxicological effects

ailable data, the classification criteria are not i

· LD/L	.C50 va	alues that are relevant for classification:
CAS	: 7664-	93-9 sulphuric acid
Oral		2140 mg/kg (rat) (IUCLID)
		510 mg/m³/2h (rat) IUCLID

· Primary irritant effect:

· on the skin: Causes skin irritation.

on the eye: Causes serious eye irritation.

Information on components:

Skin irritation testing performed on 10% sulfuric acid showed slight to no irritation effects (GESTIS).

CAS 7664-93-9: chronic: dermatitis

· Sensitization: Based on available data, the classification criteria are not met.

Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 7664-93-9 sulphuric acid	1
· NTP (National Toxicology Program)	
CAS: 7664-93-9 sulphuric acid	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

Other information: see section 8 / 15

Cancer Status of Sulfuric acid: The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a known human carcinogen, (IARC category 1). This classification applies only to mists containing sulfuric acid and not to sulfuric acid or sulfuric acid solutions. A2 (Suspected for humans) by ACGIH

· Synergistic Products: None

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): The following statements refer to the mixture:

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

In case of an acute molybdenum(VI) intoxication: diarrhoea, anaemia, fatigue, loss of appetite.

Mists may be irritant to the mucous membranes and upper respiratory tract. Sulfuric acid: erosion of the teeth, cancer

• Experience with humans: Mo(VI): Can cause liver, kidney damages.

12 Ecological information

· Toxicity

• Aquatic toxicity:	
---------------------	--

•	•
CAS:	7664-93-9 sulphuric acid
	>100 mg/l/48h (Daphnia magna) (OECD 202) (ECHA)
LC50	16–29 mg/l/96h (bluegill) (Merck)

- Bacterial toxicity: sulfates toxic > 2.5 g/l
- Other information:
- Toxic for fish:
- sulfates > 7 g/l
- molybdenum compounds in general: > 25 mg/l
- NH₄⁺ > 0.3 mg/l

Persistence and degradability .

• Other information:

Mixture of inorganic compounds.

Methods for the determination of biodegradability are not applicable to inorganic substances.

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Other adverse effects Avoid transfer into the environment.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN2796	
UN proper shipping name		
DOT	Sulfuric acid mixture	
IMDG, IATA	SULPHURIC ACID mixture	

(Contd. of page 5)

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

 Transport hazard class(es) DOT, IMDG, IATA Image: Second Seco		(Contd. of page 6
Class	· Transport hazard class(es)	
Class	· DOT. IMDG. IATA	
Label 8 Packing group II • DoT, IMDG, IATA II • Environmental hazards: Not applicable. • Special precautions for user Warning: Corrosive substances • Danger code (Kemler): 80 • EMS Number: F-A,S-B • Segregation groups Acids • Stowage Category B • Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. • Transport/Additional information: DOT • DOT On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L • IMDG Limited quantities (LQ) 1L • Excepted quantities (EQ) 1L		
Packing group II DOT, IMDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Corrosive substances Danger code (Kemler): 80 EMS Number: F-A, S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG IL Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	· Class	8 Corrosive substances
DOT, IMDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Corrosive substances Danger code (Kemler): 80 EMS Number: F-A,S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: Not applicable. DOT On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG 1L Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	[.] Label	8
Environmental hazards: Not applicable. Special precautions for user Warning: Corrosive substances Danger code (Kemler): 80 EMS Number: F-A,S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: Not applicable. DOT On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG IL Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
Special precautions for user Warning: Corrosive substances Danger code (Kemler): 80 EMS Number: F-A,S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG 1L Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	· DOT, IMDG, IATA	II
Danger code (Kemler): 80 EMS Number: F-A,S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG 1L Excepted quantities (EQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	· Environmental hazards:	Not applicable.
EMS Number: F-A,S-B Segregation groups Acids Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG 1L Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	· Special precautions for user	Warning: Corrosive substances
 Segregation groups Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Quantity limitations IMDG Limited quantities (LQ) Excepted quantities (EQ) Acids Acids Acids B Code: E2 Maximum net quantity per inner packaging: 30 ml 		
Stowage Category B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: • DOT • Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L • IMDG 1L • Excepted quantities (EQ) 1L • Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml 		
and the IBC Code Not applicable. Transport/Additional information:		
 Transport/Additional information: DOT Quantity limitations IMDG Limited quantities (LQ) Excepted quantities (EQ) IL Code: E2 Maximum net quantity per inner packaging: 30 ml 	Transport in bulk according to Annex II of MARPOL	
 DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml 	and the IBC Code	Not applicable.
 Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml 	• Transport/Additional information:	
IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
· Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
• Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		11
Maximum net quantity per inner packaging: 30 ml		
		0040.22
		Maximum net quantity per outer packaging: 500 ml

*15 Regulatory information

 $^{\rm o}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\rm o}$ Sara

· Section 355 (Extremely hazardous substances):	
CAS: 7664-93-9 sulphuric acid	
· Section 313 (Specific toxic chemical listings):	
CAS: 7664-93-9 sulphuric acid	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· New Jersey Right-to-Know List:	
CAS: 7664-93-9 sulphuric acid	
· New Jersey Special Hazardous Substance List:	
CAS: 7664-93-9 sulphuric acid	CA, CO, R2
	(Contd. on page 8 US

(Contd. of page 7)

Е

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 01/23/2019

Reviewed on 01/23/2019

Trade name: Ammonium Molybdate Solution (Silica method 1)

· Pennsylvania Right-to-Know List:

CAS: 7664-93-9 sulphuric acid

· Pennsylvania Special Hazardous Substance List:

CAS: 7664-93-9 sulphuric acid

· Other Regulations

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Information about limitation of use: Employment restrictions concerning young persons must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

· Date of preparation / last revision 01/23/2019 / 1

· Abbreviations and acronyms:

OECD: Organisation for Economic Co-operation and Development STOT: specific target organ toxicity SE: single exposure RE: repeated exposure EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration ACGIH[®] - American Conference of Governmental Industrial Hygienists •A1 - Confirmed human carcinogen •A2 - Suspected human carcinogen •A3 - Confirmed animal carcinogen with unknown relevance to humans •A4 - Not classifiable as a human carcinogen ·A5 - Not suspected as a human carcinogen IARC - International Agency for Research on Cancer Group 1 - Carcinogenic to humans •Group 2A - Probably carcinogenic to humans •Group 2B - Possibly carcinogenic to humans Group 3 - Not classifiable as to carcinogenicity to humans •Group 4 - Probably not carcinogenic to humans NTP - National Toxicology Program, U.S. Department of Health and Human Services •Group K - Known to be Human Carcinogens •Group R - Reasonably Anticipated to be Human Carcinogens IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Met. Corr.1: Corrosive to metals - Category 1 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· Sources

Data arise from safety data sheets, reference works and literature. IUCLID (International Uniform Chemical Information Database) GESTIS- Stoffdatenbank (Substance Database, Germany)

** Data compared to the previous version altered.