

Lovibond® Water Testing Tintometer® Group



SensoDirect Con 110 (Set)



- High measuring accuracy
- Light weight
- Protective casing
- Large digital display

Part Number: 722300

Different parameters

SensoDirect 110 series meters can be used to measure pH, salt and conductivity.

Housing

The protective armor does not guarantee a secure grip but also protection against falls. The stand attached to the back of the housing can also be used as a hanger or belt clip.

"Hold" function included

Data gained is virtually "frozen" on the display by this function. This not only makes it easier to read the results, it also improves reproducibility.

Automatic battery check

So you do not experience unpleasant surprises with the battery, the level is constantly monitored. This way, you can always change the battery in good time.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Public | Pool Services

SensoDirect Con 110 (Set)

High-quality, battery-operated handheld instrument for the determination of conductivity.

Variable in use and user-friendly in operation

Measuring Range

Test Name	Measuring Range
Conductivity	0.001 - 1.999 mS/cm
Conductivity	0.01 - 19.99 mS/cm

Technical Data

Measuring Range	0,001 - 1,999 mS/cm, 0,01 - 19,99 mS/cm
Auto – OFF	Yes
Power Supply	9 V-block
Portability	Portable
Protection Class	IP 30
Compliance	CE
Dimensions	110 x 34 x 208 mm
Weight	380 g

Delivery Scope

- Instrument in a sturdy plastic case
- Battery
- Conductivity sensor
- Instruction manual
- Warranty information

Title	Part Number
Calibration solution 1413 $\mu\text{S}/\text{cm}$, 500 ml, traceable to N.I.S.T	722250
Conductivity cell, 1 m cable	724400
Case incl. foam for SensoDirect Con 110	725040
Conductivity Solution (1413 $\mu\text{S}/\text{cm}$) - 90 ml - traceable to N.I.S.T.	726654
Conductivity Solution (12.88 mS/cm) - 90 ml - traceable to N.I.S.T.	726684

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice

Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies