Lovibond® Water Testing

Tintometer® Group



Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 03/01/2022 Reviewed on 03/01/2022

1 Identification

- · Product identifier
- · Trade name: Vario Sulfide Reagent 1
- · Catalogue number: 424186, 531310
- · Application of the substance / the mixture: Reagent for water analysis
- · Manufacturer/Supplier:

Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA

phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany

· Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Corrosive to Metals 1 H290 May be corrosive to metals.

Skin Corrosion 1A H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



GHS05

· Signal word Danger

· Hazard-determining components of labeling:

sulphuric acid 60 %

N,N-dimethylbenzene-1,4-diammonium sulphate

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.

P234 Keep only in original container.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a poison center/doctor.

· Other hazards

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Acid burns have to treated immediately, as it may otherwise cause badly curing wounds.

- US

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Mixtures
 Description: sulfuric acid solution

Composition and Information on Ingredients:

Cancer Status IARC: Strong inorganic acid mists containing sulphuric acid can cause cancer.

Percent ranges are used due to the confidential product information.

| ſ | CAS: 7664-93-9 | sulphuric acid | 50–60% |
|---|----------------------------|--|--------|
| | EINECS: 231-639-5 | ♦ Corrosive to Metals 1, H290; Skin Corrosion 1A, H314 | |
| | Index number: 016-020-00-8 | | |
| | RTECS: WS5600000 | | |
| ı | CAS: 536-47-0 | N,N-dimethylbenzene-1,4-diammonium sulphate | 0.1–1% |
| | EINECS: 208-636-2 | ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ♦ Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target | |
| | | | |
| | | Organ Toxicity - Single Exposure 3, H335 | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air.

Call a doctor immediately.

· After skin contact:

Immediately wash with polyethylene glycol 400.

Immediately rinse with plenty of water.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

· After eye contact:

Rinse opened eye for several minutes (at least 15 min) under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink 1-2 glasses of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed

burns

after inhalation:

irritations

coughing

breathing difficulty

damage to the affected mucous membranes

after swallowing:

sickness

vomiting

diarrhoea

pain

strong caustic effect

Danger:

Danger of circulatory collapse.

Danger of gastric perforation.

Danger of pulmonary edema.

Risk of serious damage to eyes.

Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- For safety reasons unsuitable extinguishing agents:

Water with full jet

(Contd. on page 3)

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 2)

--> exothermic reaction.

Special hazards arising from the substance or mixture

The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Sulfur oxides (SOx)

Nitrogen oxides (NOx)

Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

· Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

Use respiratory protective device against the effects of fume/dust/aerosol.

- · Advice for emergency responders: Protective equipment: see section 8
- · Environmental precautions: Do not allow product to reach sewage system or any water course.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralizing agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

· Advice on safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Prevent formation of aerosols.

· Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

· Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Keep only in original container.

Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

Store away from flammable substances.

Store away from reducing agents.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

Protect from exposure to the light.

Protect from humidity and water.

(Contd. on page 4)

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 3)

- · Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

| CAS: 7664-9 | 7664-93-9 sulphuric acid | | | |
|-------------|--|--|--|--|
| PEL (USA) | Long-term value: 1 mg/m³ | | | |
| REL (USA) | Long-term value: 1 mg/m³ | | | |
| TLV (USA) | Long-term value: 0.2* mg/m³ *as thoracic fraction, A2 | | | |
| | Long-term value: 0.2 mg/m³ thoracic, ACGIH A2; IARC 1 | | | |
| EV (Canada) | Long-term value: 0.2 mg/m³ | | | |

- · Additional information: The lists that were valid during the creation were used as basis.
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

· Personal protective equipment:

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

- · Breathing equipment: Use respiratory protective device against the effects of fume/dust/aerosol.
- Recommended filter device for short term use: Combination filter B-P2
- · Protection of hands:

Acid resistant gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.35 mm

Penetration time of glove material

Value for the permeation: Level < 1 (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

Use protective goggles that have been tested and approved in accordance with government standards (like NIOSH).

- · Body protection: Acid resistant protective clothing
- · Limitation and supervision of exposure into the environment:

Do not allow product to reach sewage system or any water course.

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · Appearance:

· Form / Physical state: Solution · Color: Colorless Odorless · Odor: · Odor threshold: Not applicable. · pH-value at 20°C (68°F):

Strongly acidic · Melting point/freezing point: Not determined. Initial boiling point and boiling range: Not determined. · Flash point: Not applicable.

The product is not combustible. · Flammability (solid, gas):

Ignition temperature: Not applicable.

Printing date 03/01/2022 Reviewed on 03/01/2022

< 0.5 %

Trade name: Vario Sulfide Reagent 1

(Contd. of page 4)

· Decomposition temperature: Not applicable.

· Auto-ignition temperature: Product is not self-igniting.

Danger of explosion:
 Product does not present an explosion hazard.

· Flammability or explosive limits:

Lower: Not applicable.
 Upper: Not applicable.
 Oxidizing properties: CAS 7644-93-9: Oxidizing potential
 Vapor Pressure: Not determined.

Density at 20°C (68°F): 1.5 g/cm³ (12.52 lbs/gal)

Relative density:
Vapor density:
Not determined.
Evaporation rate:
Not determined.

Solubility(ies)

· Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not applicable (mixture).

· Viscosity:

· **Kinematic:** Not determined.

Other informationSolids content:

Solvent content:
Organic solvents:
Water:
40-50 %

Information with regard to physical hazard classes May be corrosive to metals.

10 Stability and reactivity

- · Reactivity see section "Possibility of hazardous reactions"
- · Chemical stability Stable at ambient temperature (room temperature).
- · Possibility of hazardous reactions

Corrosive action on metals.

Reacts with metals forming hydrogen (Danger of explosion!)

When diluting, always add acid to water, never vice versa.

Diluting or dissolving in water always causes rapid heating.

Reacts with acids and alkali (lyes).

Reacts with reducing agents.

Reacts with oxidizing agents.

Reacts with peroxides.

Reacts with halogenated compounds.

Reacts with ammonia (NH₃).

- · Conditions to avoid Strong heating (decomposition)
- · Incompatible materials:

metals

combustible materials

organic solvents

· Hazardous decomposition products: see section 5

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

| | · Acute toxicity estimate (ATE _(MIX)) - Calculation method: | | | | |
|--|---|------------------------------------|--|--|--|
| | | 3304 mg/kg (.) | | | |
| Inhalative | GHS ATE _{(MIX} | 204 mg/l/4h (aerosol (dust, mist)) | | | |
| · LD/LC50 values that are relevant for classification: | | | | | |
| CAS: 7664-93-9 sulphuric acid | | | | | |
| Oral | | 40 mg/kg (rat) | | | |
| | (IL | JCLID) | | | |

(Contd. on page 6)

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

· Primary irritant effect:

- · on the skin: Causes severe skin burns.
- · on the eye:

Causes serious eye damage.

Risk of blindness!

- · Sensitization: Based on available data, the classification criteria are not met.
- Carcinogenic categories

| · IARC (International Agency for Research on Cancer) | | | | | |
|---|---|--|--|--|--|
| CAS: 7664-93-9 sulphuric acid | 1 | | | | |
| · NTP (National Toxicology Program) | | | | | |
| CAS: 7664-93-9 sulphuric acid | K | | | | |
| · OSHA-Ca (Occupational Safety & Health Administration) | | | | | |
| None of the ingredients is listed. | | | | | |

· Other information:

see section 8 / 15

Cancer Status of Sulfuric acid: The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a known human carcinogen, (IARC category 1). This classification applies only to mists containing sulfuric acid and not to sulfuric acid or sulfuric acid solutions.

A2 (Suspected for humans) by ACGIH

- Synergistic Products: None
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): The following statements refer to the mixture:
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

· Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach. The aerosol is corrosive to the eyes, the skin and the respiratory tract. Inhalation of aerosols may cause lung oedema. Sulfuric acid: erosion of the teeth, cancer

CAS: 7664-93-9 sulphuric acid

(source: GESTIS)

Main toxic effects

Acute: Irritation up to chemical burns to the mucous membranes and skin, danger of serious damage to the eyes and lungs Chronic: Irritation to the eyes and airways, erosion of the teeth, damage to the skin

Further Information:

Concentrated S. differs considerably from dilute Sulfuric acid with regard to chemical properties and effects. With increased dilution Sulfuric acid acts less aggressively.

-US-

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 6)

12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 7664-93-9 sulphuric acid

EC50 >100 mg/l/48h (Daphnia magna) (OECD 202)

(ECHA)

LC50 16-29 mg/l/96h (bluegill)

(Merck)

- Bacterial toxicity: sulfates toxic > 2.5 g/l
- Other information:

Toxic for fish:

sulfates > 7 g/l

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Avoid transfer into the environment.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

| · UN-Number · DOT, IMDG, IATA | UN1830 | |
|----------------------------------|------------------------|--|
| · UN proper shipping name | | |
| · DOT | Sulfuric acid mixture | |
| · IMDG, IATA | SULPHURIC ACID mixture | |
| · Transport hazard class(es) | | |
| · DOT | | |
| | | |



· Class 8 Corrosive substances · Label 8

· IMDG, IATA



· Class 8 Corrosive substances · Label 8

· Packing group

· DOT, IMDG, IATA

(Contd. on page 8)

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 7)

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Hazard identification number (Kemler code):
 EMS Number:
 Segregation groups
 80
 F-A,S-B
 Strong acids

· Stowage Category C

Stowage Code SW15 For metal drums, stowage category B. Segregation Code SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides

Transport in bulk according to Annex II of MARPOL73/78

and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations**On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L

·IMDG

· Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (Extremely hazardous substances):

CAS: 7664-93-9 sulphuric acid

· Section 313 (Specific toxic chemical listings):

CAS: 7664-93-9 sulphuric acid

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

CAS: 7664-93-9 sulphuric acid

New Jersey Special Hazardous Substance List:

CAS: 7664-93-9 sulphuric acid CA, CO, R2

· Pennsylvania Right-to-Know List:

CAS: 7664-93-9 sulphuric acid

· Pennsylvania Special Hazardous Substance List:

CAS: 7664-93-9 sulphuric acid

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

Printing date 03/01/2022 Reviewed on 03/01/2022

Trade name: Vario Sulfide Reagent 1

(Contd. of page 8)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · Information about limitation of use: Employment restrictions concerning young persons must be observed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

· Date of preparation / last revision 03/01/2022 / -

Abbreviations and acronyms:

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration

ACGIH® - American Conference of Governmental Industrial Hygienists

•A1 - Confirmed human carcinogen

•A2 - Suspected human carcinogen

•A3 - Confirmed animal carcinogen with unknown relevance to humans

•A4 - Not classifiable as a human carcinogen •A5 - Not suspected as a human carcinogen

IARC - International Agency for Research on Cancer
•Group 1 - Carcinogenic to humans

•Group 2A - Probably carcinogenic to humans

•Group 2B - Possibly carcinogenic to humans

•Group 3 - Not classifiable as to carcinogenicity to humans

•Group 4 - Probably not carcinogenic to humans NTP - National Toxicology Program, U.S. Department of Health and Human Services •Group K - Known to be Human Carcinogens

•Group R - Reasonably Anticipated to be Human Carcinogens

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Corrosive to Metals 1: Corrosive to metals - Category 1

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A
Skin Irrititation 2: Skin corrosion/irritation – Category 2
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Data arise from safety data sheets, reference works and literature.

ECHA: European CHemicals Agency http://echa.europa.eu

GESTIS- Stoffdatenbank (Substance Database, Germany)