

# Lovibond® Colour Measurement

## Tintometer® Group



## TG 268 Gloss Meter



### Handheld and Portable

Weighing only 350 grams, the TG 268 is the perfect lightweight portable gloss meter. Its compact and ergonomic design offers easy one-handed operation, helping to prevent operator fatigue. Offering the possibility of 1,000 measurements with 8 hours battery life enables the TG 268 to be used anywhere on site for a prolonged period of time.

### Flexibility

The TG 268 offers the user high flexibility. With detector angles of 20°/ 60°/ 85° the TG 268 can measure low, medium and high gloss levels on a wide range of materials. To enhance flexibility even further, basic, statistical and continuous measurement modes are available to ensure the TG 268 can be set perfectly to the user's needs.

### Calibration

Every TG 268 is supplied with a calibration plate and easy to use on screen calibration guide making the whole procedure fast and simple for the user.

### FREE Software

As standard, the TG 268 comes with a FREE PC software package. The OnGloss software allows for a detailed data analysis which can then be shared or printed via the optional micro printer accessory.

### Suitable for Multiple Standards

The TG 268 is able to support the following standard gloss levels: ASTM D523; ASTM C584; ASTM D2457; BS3900 D5; DIN 67530; DIN EN ISO 2813; EN ISO 7668 and JIS Z 8741.

- Handheld Gloss Meter Designed to Give Fast, Precise and Accurate Gloss Readings
- Three Measurement Angles of 20°, 60° and 85°
- Compare Data Quick and Easy With a Data Storage Capacity of Over 5000 Data Sets
- OnGloss Software Included for FREE – Perfect for Detailed Data Analysis

货号: 403045

### 应用

塑料 | 日用品 | 涂料 | 纺织品

### TG 268 Gloss Meter

The TG 268 is a cost-effective handheld gloss meter with a high-end specification. The ergonomic design, flexibility and intuitive touch screen technology makes the TG 268 equal in sophistication to any handheld gloss meter on the market. The meter comes with the ability to select 20°, 60° and 85° measurement angles and the choice of multiple measuring modes making it ideal for quality control in the production process of many industries.

## Technical Data

颜色类型	Opaque
显示	TFT 3.5 inch, capacitive touch screen
数据接口	USB RS 232
测量范围	0-10个光泽度单位，重现性±0.1个光泽度单位，重现性±0.2个光泽度单位。 10 - 100个光泽度单位，重现性±0.2个光泽度单位，重现性±0.5个光泽度单位。 100 - 2000个光泽度单位，重现性±0.2%光泽度单位，重现性±0.5%光泽度单位。
Measuring Angle	20° / 60° / 85°
测量区域	20°: 10 x10 ; 60°: 9 x15 ; 85°: 5 x 36
测量范围	20°: 0 - 2000 GU ; 60°: 0 - 1000 GU ; 85°: 0 - 160 GU
Division Value	0.1 GU
内置存储器	Basic Mode: 1000 ; Statistical Mode: 5000 ; Continuous Mode: 5000
测量时间	1.0 s
电池寿命	> 1000 times (within 8 hours)
便携性	手提
多语言操作界面	英文
尺寸	160 x 90 x 75 mm

## 标准配置文本

- TG 268 Handheld Gloss Meter
- OnGloss Software (PC)
- Calibration Plate
- USB Cable
- External DC Power Supply
- USB Stick with User Manuals in English, French, German, Spanish, Portuguese and Chinese
- Sturdy Carrying Case

**Tintometer GmbH**  
 Lovibond® Water Testing  
 Schleefstraße 8-12  
 44287 Dortmund  
 Tel.: +49 (0)231/94510-0  
 sales@lovibond.com  
 www.lovibond.com  
 德国

**The Tintometer Limited**  
 Lovibond House  
 Sun Rise Way  
 Amesbury, SP4 7GR  
 Tel.: +44 (0)1980 664800  
 sales@lovibond.uk  
 www.lovibond.com  
 英国

**Tintometer China**  
 9F, SOHO II C.  
 No.9 Guanghualu,  
 Chaoyang District,  
 Beijing, 100020  
 Customer Care China Tel.: 4009021628  
 Tel.: +86 10 85251111 Ext. 330  
 Fax: +86 10 85251001  
 chinaoffice@tintometer.com  
 www.lovibond.com  
 中国

**Tintometer South East Asia**  
 Unit B-3-12, BBT One Boulevard,  
 Lebuh Nilam 2, Bandar Bukit Tinggi,  
 Klang, 41200, Selangor D.E  
 Tel.: +60 (0)3 3325 2285/6  
 Fax: +60 (0)3 3325 2287  
 lovibond.asia@tintometer.com  
 www.lovibond.com  
 马来西亚

**Tintometer Brazil**  
 Caixa Postal: 271  
 CEP: 13201-970  
 Jundiaí – SP  
 Tel.: +55 (11) 3230-6410  
 sales@lovibond.us  
 www.lovibond.com.br  
 巴西

**Tintometer Inc.**  
 6456 Parkland Drive  
 Sarasota, FL 34243  
 Tel: 941.756.6410  
 Fax: 941.727.9654  
 sales@lovibond.us  
 www.lovibond.us  
 美国

**Tintometer India Pvt. Ltd.**  
 Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
 Sanathnagar Industrial Estate,  
 Hyderabad, 500018  
 Telangana  
 Tel: +91 (0) 40 23883300  
 Toll Free: 1 800 599 3891/ 3892  
 indiaoffice@lovibond.in  
 www.lovibondwater.in  
 印度

**Tintometer Spain**  
 Postbox: 24047  
 08080 Barcelona  
 Tel.: +34 661 606 770  
 sales@tintometer.es  
 www.lovibond.com  
 西班牙