

Lovibond® Water Testing

Tintometer® Group



Hydrogen Peroxide Drop Test Kit

Control the level of hydrogen peroxide



The high quality Lovibond® General Drop Test Kits and reagents are available in a wide range of parameter specific options to suit many analytical requirements. Each self-contained Kit is housed in its own rugged carry case and comes complete with all necessary equipment such as instructions, reagents, syringe and test bottle or test cell for 100 tests.

Derived from laboratory burette methods, the Lovibond® drop test range forms an integral part of the analytical program. The reagents are quick to use and give results fast.

- Ideal for mobile treatment engineers
- Compact & portable design
- Easy to follow instructions including pictograms
- Complete with all necessary equipment

Referencia No: 56K700290

Industria

Otras industrias

Aplicaciones

Agua de refrigeración | Control de desinfección

Hydrogen Peroxide Drop Test Kit

Lovibond® offers a wide range of single parameter Drop Test Kits for individual test requirements. They are for use in various water testing applications including potable water, process water, industrial boilers & cooling systems, swimming pool and waste water treatment. Drop Tests work by a simple colour change and are derived from laboratory burette methods.

Rango de medición

Test Name	Rango de medición
Hydrogen Peroxide	15 - 500 mg/L H ₂ O ₂

Volumen de suministroo

- Plastic case
- Hydrogen Peroxide Buffer HP1
- Hydrogen Peroxide HR Titrant HP2
- Hydrogen Peroxide LR Titrant HP3
- Syringe plastic, 20 mL
- Titration jar with cap, plastic, 60 mL
- Instruction manual

Título	Referencia No
Jeringuilla, plástico, 20 mL	56A006501
Recipiente de valoración con tapa, plástico, 60 mL	56A006701

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Alemania

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Reino Unido

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malasia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brasil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Estados Unidos de América

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
España

Nos reservamos el derecho de cambios técnicos

Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies