

Lovibond® Water Testing Tintometer® Group



Cooling Water Weekly Test Kit

For regular monitoring of cooling water



The Test Kit contains all equipment and test reagents required to optimise treatments and regularly monitor critical control parameters quickly, safely and accurately, ensuring optimum output and efficiency.

The Lovibond® Cooling Weekly Test Kit is designed for use on cooling towers and many types of closed water systems such as chilled water circuits and heating systems.

The kit will enable end users to complete tests in between engineers visits. It should be used to monitor water conditions to ensure that the systems are under control and do not exhibit signs of corrosion, scaling or microbiological fouling.

- Monitor parameters quickly, safely and accurately
- Ensures optimum output and efficiency
- Control correct levels and dosing
- Easy, daily analysis

Referencia No: 56K701100

Industria

Industria naval | Otras industrias

Aplicaciones

Agua de refrigeración

Cooling Water Weekly Test Kit

All cooling systems work on the same principle: Water is circulated by a pump through a pipe system to remove excess heat. No matter whether it is an open or closed system: Water is always lost, new water must be added. So chemical changes occur or microorganisms and deposits form. There are therefore certain parameters that should be checked regularly in order to avoid problems and extend the life of the systems.

Rango de medición

Test Name	Rango de medición	Método químico
Bromo T	0 - 5 mg/L Br ₂	DPD
Conductivity	0 - 20 mS/cm	
Dureza, total	5 - 600 mg/L CaCO ₃	
Hardness Calcium	5 - 600 mg/L CaCO ₃	
pH	0 - 14	

Volumen de suministroo

- Plastic case
- SD40 Multi Pocket Tester
- Checkit Comparator
- Checkit Disc Bromine
- Syringe plastic, 20 mL
- Titration jar with cap, plastic, 60 mL
- 2 plastic vials 10mL with lid
- 100 DPD No. 1 Rapid
- Hardness Total Buffer TH2
- Hardness LR Titrant TH3
- Hardness HR Titrant TH4
- Hardness Total Indicator TH1P
- Calcium Hardness Indicator CH1P
- Calcium Hardness Buffer CH2
- pH Buffer 4
- pH Buffer 7
- pH Buffer 10
- 1413 μ S Standard Conductivity Solution
- Instruction manual

Título	Referencia No
Comparator CHECKIT®	145000
Jeringuilla, plástico, 20 mL	56A006501
Recipiente de valoración con tapa, plástico, 60 mL	56A006701

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Alemania

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Reino Unido

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malasia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brasil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Estados Unidos de América

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
España

Nos reservamos el derecho de cambios técnicos

Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies