

# Lovibond® Water Testing Tintometer® Group



## Disinfection Test Kit (combined)

For disinfection control in all applications



The Lovibond® Combined Disinfection Test Kit should be used in all applications where a system water disinfection is being carried out to ensure full compliance with current regulations.

The comprehensive Kit allows the determination of both chlorine (as  $\text{Cl}_2$ ), chlorine dioxide ( $\text{ClO}_2$ ) and hydrogen peroxide (as  $\text{H}_2\text{O}_2$ ) at both low & high levels which are required during a system disinfection.

High levels of disinfectant need to be monitored during the procedure to ensure that sufficient disinfectant has been achieved at the tank and all subsequent outlet.

Low levels need to be monitored to ensure that (if appropriate) the system has been fully flushed to remove all disinfectants and the system water is back to the same as mains water quality.

The disinfectant levels must be recorded to ensure full compliance with standards.

- Determination of all common disinfection methods
- Monitoring the correct concentration for your system
- Control high & low disinfection levels
- Complete Kit for economic & fast results

Code: 56K701160

### Industrie

Autres industries | Municipalités

### Applications

Contrôle de la désinfection | Eau de refroidissement

### Disinfection Test Kit (combined)

Building owners and management teams as well as water treatment companies have to control several commercial buildings with different water systems in compliance with current regulations. No matter whether hot or cold-water services have to be monitored: They have the obligations to take care for safe water.

Our Disinfection Test Kits assist to control formation of biofilms, growth of Legionella bacteria or correct strength of disinfectants. Additionally it avoids system blockages or deposit corrosion and material damage.

The Lovibond® Disinfection Combined Test Kit includes all testing instruments and reagents for monitoring different disinfection methods.

## Gamme de mesure

Test Name	Gamme de mesure
Chlore (libre)	1 - 300 mg/L Cl <sub>2</sub>
Chlore HR	10 - 200 mg/L Cl <sub>2</sub>
Chlorine Dioxide	0.16 - 600 mg/L ClO <sub>2</sub>
Hydrogen Peroxide test strips	0.5 - 100 mg/L H <sub>2</sub> O <sub>2</sub>
Peroxyde d'hydrogène	15 - 500 mg/L H <sub>2</sub> O <sub>2</sub>
pH	7 - 14 pH

## Contenu de livraison

- Plastic case
- pH Test Strips, pH 7-14, plastic
- Chlorine HR Test Strips, 10-200 mg/L
- Hydrogen Peroxide Test Strips, 0.5-100 mg/L
- Free Chlorine Buffer FCL1
- Free Chlorine LR Titrant FCL2
- Free Chlorine HR Titrant FCL3
- Chlorine Dioxide Buffer CDO1
- Hydrogen Peroxide Buffer HP1
- Tannin Titrant TN2
- Hydrogen Peroxide HR Titrant HP2
- Chlorine Dioxide Titrant CDO2
- Chlorine Dioxide Titrant CDO3
- Syringe plastic, 20 mL
- Titration jar with cap, plastic, 60 mL
- Instruction manual

Titre	Code
Seringue, plastique, 20 mL	56A006501
Réceptif de titrage avec couvercle, plastique, 60 mL	56A006701
Réceptif de titrage avec couvercle, plastique, 250 mL	56A010501

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Allemagne

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
Royaume-Uni

### Tintometer China

Room 1001, China Life Tower  
16 Chaoyangmenwai Avenue,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 App. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
Chine

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaisie

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brésil

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
États-Unis

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
Inde

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Espagne