

Lovibond® Water Testing

Tintometer® Group



Water Safety Kit Chemical

Uitgerust voor alle vereisten



You need safe, fast and reliable test results in difficult situations like disasters or potable water monitoring in rural environments without laboratories? The Lovibond® Water Safety Kit Chemical offers the most important methods and equipment in one case, designed to accompany you in each situation.

It comprises our MD 600 photometer, TB 211 IR turbidity meters and SD 50 AND SD 70 pocket electrochemistry meters. This kit can be used in conjunction with the Water Safety Kits Microbiology to provide a complete suite of tests for potability of water.

The kit comes with reagents for Chlorine, Ammonia, Nitrite, Nitrate, pH, Conductivity, Turbidity but can be expanded using our reagent packs to include any of the tests for the MD 600.

- Analysis of most important chemical parameters
- Complete test equipment in conjunction with Water Safety Kits Microbiology
- No further test equipment required for chemical analysis

Bestelnr.: 56K681253

Industrie

Chemische industrie | Energieleveranciers | Farmaceutische industrie | Gemeenten | Ngo | Olie-industrie | Openbaar zwembad | Overige industrieën | Privézwembad | Scheepvaart | Voedingsmiddelen- en drankenindustrie | Zwembadservice

Applikation

Afvalwaterzuivering | Behandeling drinkwater | Controle desinfecteermiddel | Controle zwembadwater | Ketelwater | Koelwater | Zuivering- vervuild water

Water Safety Kit Chemical

Take everything you need for chemical analysis of potable water quality in one hand. This Water Safety Kit is the smallest in the range, portable in a rugged, waterproof case with 200 reagents for each parameter, allowing numerous measurements for its small footprint.

It is easy to use even by nonprofessional operators due to simple pictorial instructions.

User

Non Profit Organizations (NGO's) | Medical research and development | Institutes, Universities, Schools | World Health Organization (WHO)

Meetbereik

Test Name	Meetbereik	Chemische methode
Ammonium T	0.02 - 1 mg/L N	Indofenolblauw
Chloor T	0.01 - 6.0 mg/L Cl ₂ ^{a)}	DPD
Conductivity	0 - 20 mS/cm	
Nitraat T	0.08 - 1 mg/L N	Zinkreductie / NED
pH	0 - 14	
Turbidity	0.01 - 1100 NTU	

Technische gegevens

Afmetingen 411 x 168 x 322 mm

Gewicht met verpakking 4.5 kg

Omschrijving	Bestelnr.
Satz Trübungsstandards T-CAL (<0,1, 20, 200, 800 NTU)	194150
Plastic beker, gegraduateerd, 100 ml, met deksel	385130
Plastic beker, gegraduateerd, 30 ml, met deksel	385132
ValidCheck Chloor 1,5 mg/l	48105510
Roerstaaf en poederlepel	56A006601
Rugzak voor Water Safety Kits	56A01400
KS3-pH 10 bufferoplossing 65 ml	56L000365
KS6-pH 4 bufferoplossing 65 ml	56L000665
KS9-pH 7 bufferoplossing 65 ml	56L000965
KS16-1413US Standaardgeleidbaarheidsoplossing	56L001665

Leveromvang

- MD 600 Photometer
- TB 211 IR Turbidimeter
- SD 70 Conductivity Meter
- SD 50 pH Meter
- KS16 (65 ml)
- KS9 (65 ml)
- KS6 (65 ml)
- KS3 (65 ml)
- 250 DPD No.1 Photometer tablet reagents
- 250 DPD No.3 Evo Photometer tablet reagents
- Nitrate Test Powder R282, 15 g
- 100 Nitrate Test tablet reagents
- Nitrate Test Tube Cali., 20 ml
- 250 Nitrite LR tablet reagents
- 250 Ammonia No.1 tablet reagents
- 250 Ammonia No.2 tablet reagents
- Shaker Tube Plastic, 30 ml
- DB513 Shaker Tube with lid, 100 ml
- Stirring Rod & Powder Scoop
- 3 Round Cuvette 24 mm with lid and seal
- 2 Round Cuvette 24 mm x 54 mm
- 2 Lid 24 mm, black
- T-CAL Turbidity Standard < 0.1 NTU
- T-CAL Turbidity Standard 20 NTU
- T-CAL Turbidity Standard 200 NTU
- T-CAL Turbidity Standard 800 NTU
- Instruction manual for Water Safety Kit Chemical
- Case

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Duitsland

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Verenigd Koninkrijk

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Maleisië

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazilië

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Verenigde Staten

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spanje