

Lovibond® Water Testing Tintometer® Group



Disinfection Chlorine Dioxide Test Kit

Determination of chlorine dioxide for disinfection



Chlorine dioxide (ClO_2) kills microorganisms in the water and has a stronger disinfection effect against germs, viruses, bacteria, fungi and algae than the most commonly used chlorine. Legionella are also reliably removed.

In addition, there is the gradual degradation effect on the biofilm as a breeding ground for legionella even at low doses.

The disinfection effect of chlorine dioxide is also almost independent of the pH value. It does not form chloramines and is largely odourless and tasteless.

- On-site testing before and after disinfection works
- Non DPD method for the determination of chlorine dioxide
- For control in the treatment of microorganisms
- Simple for use by both technical and non-technical operators

Bestelnr.: 56K701140

Industrie

Gemeenten | Overige industrieën

Applikation

Controle desinfecteermiddel | Koelwater

Disinfection Chlorine Dioxide Test Kit

For commercial buildings, especially dormant premises, industry organisations recommend in many countries regular maintenance procedures for hot & cold-water services to prevent infection with bacteria, biofilms & material damage through misdosing.

The Lovibond® Disinfection Chlorine Dioxide Test Kit assists you with testing instruments and reagents for monitoring the correct dosing level.

Chlorine dioxide is stronger than chlorine and guarantees to reach outlying corners of branches water systems even for Legionella prevention.

Meetbereik

Test Name	Meetbereik
Chlorine Dioxide	0.16 - 600 mg/L ClO_2
pH	0 - 14 pH

Leveromvang

- Plastic case
- pH Test Strips, pH 7-14, plastic
- Chlorine Dioxide Buffer CDO1
- Chlorine Dioxide Titrant CDO2
- Chlorine Dioxide Titrant CDO3
- Syringe, plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Instruction manual

Omschrijving	Bestelnr.
Spuit, plastic, 20 mL	56A006501
Titratievat met deksel, kunststof, 250 mL	56A010501

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Duitsland

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Verenigd Koninkrijk

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Maleisië

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazilië

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Verenigde Staten

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spanje