

Lovibond® Water Testing Tintometer® Group



TB350 WL Portable Turbidimeter, EPA

Laboratory accuracy meets portability



- Reads up to 4000 NTU without the need for dilutions
- Fast Settling Mode increases accuracy of readings with large or heavy particles
- Easily save and recall measurement data sets
- US EPA Approved (alternative to method 180.1)

Part Number: 194310

Ideal for field and environmental testing, the TB350 WL turbidimeter delivers the most reliable measurements for low range to high range samples without sacrificing accuracy. Featuring the patent-pending Multipath 90° BLAC® sensor technology, the optical system is engineered with dual detectors to deliver a ratio reading which mitigates common measurement stability issues.

The intuitive, touchscreen interface makes it easy to perform procedures and interpret results. With function applications, you can navigate between settings and performing that function efficiently. This user interface eliminates common frustrations and prevents errors. The data logging capabilities allow you to record the testing location, operator's identification, time and date along with the measurement. Stored data can be transferred to a computer via USB.

Supplied ready-to-use with sample cells, silicone oil and calibration standards in carrying case.

At Lovibond®, we look out for the little things that make a big difference. On the surface, turbidity analysis is a simple measurement. However, there are many factors that can affect the accuracy of readings or the dependability of an instrument. We obsess about turbidity measurement so you don't have to. Our team of globally recognized turbidity experts work to anticipate and solve operators' struggles with turbidity measurement.

Industry

Municipalities

Application

Drinking Water Treatment | Pool Water Control |
Waste Water Treatment

TB350 WL Portable Turbidimeter, EPA

The TB350 WL portable turbidimeter is designed for use in the field. Distribution system monitoring, environmental testing or even labs that test a wide range of samples are ideal applications. The instrument includes features and tools to prevent common turbidity measurement mistakes and encourage best practices to ensure the best results.

Measuring Range

Test Name	Measuring Range
Turbidity	0.01 - 4000 NTU

Technical Data

Model	Model WM-040-1001 (WL)
Light Source	White LED
Regulatory Compliance	EPA approved (alternative to US EPA 180.1)
Measuring Principle	Nephelometric (Multipath 90° BLAC)
Measuring Range	0.01 - 4000 NTU (FNU)
Accuracy	± 1.8 % of reading + straylight
Stray Light	< 0.014 NTU
Display Units	NTU, FNU, Degrees, mg/L Kaolin, mg/L PSL
Reading Modes	Single, Signal Averaging, Fast-Settling
Calibration Options	Full-range calibration from 0 - 4000 NTU
Detector	Silicon Photodiode
Sample Required	10 mL (0.4 oz)
Display	Full-Colour Touchscreen
Display Size	55 x 95 mm (W x H)
Interfaces	USB-A USB-C
Data Logger	250 measurements, all calibrations, verifications and factory-restore actions
Data Transfer Format	.csv
Compliance	CE CSA FCC A RoHS TÜV UL WEE
Languages User Interface	German, English, French, Spanish, Portuguese, Chinese, Japanese, Dutch, Turkish, Polish
Languages Quick Start Guide	German, English, French, Spanish, Italian, Portuguese, Chinese, Dutch, Turkish, Russian
Languages Full User Manual	German, English, French, Spanish, Italian, Portuguese, Chinese, Dutch, Turkish, Russian
Dimensions	6.1 x 3.27 x 8.86"
Weight with Packaging	(898 g with four AA alkaline batteries)

Title	Part Number
Set turbidity standards T-CAL (5, 20, 800, 2000, 4000 NTU)	194152
Silicon oil	194295
Batteries (AA), set of 4	1950025
Cleaning cloth	197635
Sample cuvettes with black lid, Height 55 mm, ø 24 mm, set of 12	197655
Rechargeable battery pack, Ni-MH	19820-011
USB-C cable 1 m, USB-C to A	19820-081
Power supply TB series	19820-170
Brush, 11 cm length	380230
Cuvette stand for 6 round cuvettes Ø 24 mm	418951
T-CAL®-Standard, 4000 NTU, 125 ml	48012912
T-CAL®-Standard, 4000 NTU, 500 ml	48012950

Delivery Scope

- TB350 WL in case
- 2 cuvettes with lids
- 1 Cleaning cloth for cuvettes
- 1 Cleaning brush
- Silicon oil, 15 mL
- 4 Batteries (AA)
- 1 T-CAL®-Standard, 5 NTU
- 1 T-CAL®-Standard, 20 NTU
- 1 T-CAL®-Standard, 800 NTU
- 1 T-CAL®-Standard, 2000 NTU
- 1 T-CAL®-Standard, 4000 NTU
- 1 Screw driver
- 1 Quick Start Guide
- 1 Test Certificate T-CAL®
- 1 Warranty information

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain