Lovibond® Water Testing Tintometer® Group



Kit de teste, THPS, 0-100 ppm

For monitoring the broadband biocide THPS



- Specially for cooling water & other industrial applications
- Effective against Sulphate Reducing Bacteria (SRB)
- Drop tests for up to 100 tests
- Easy to handle

Artigo No: 56K701210

Versatile application

THPS stands for Tetra Hydroxymethyl Phosphonium Sulphate. It is commonly regarded as an environmentally friendly biocide that is readily degradable and has low volatility. As a broad-spectrum biocide, it is effective against the most common types of bacteria that cause problems in cooling water, especially Sulphate Reducing Bacteria (SRB). THPS is also used for the control of Legionella. It inhibits the growth of algae, bacteria, yeasts and fungi in a wide range of industrial applications.

Keeping the dosage under control

With this Test Kit you can control the THPS concentration anytime and anywhere. Our Kits are designed for mobile use directly on site. This way, you quickly have certainty about the correct dosage, because misdosing can also cause damage to the water system and the material. This will save both time and money at the same time. Our Test Kits also provide compliance with the applicable regulations.

Indústria

Outras Indústrias

Aplicação

Água de Refrigeração | Controle de Desinfecção

Kit de teste, THPS, 0-100 ppm

Microorganisms and bacteria are among the main causes of problems for cooling water and other industrial water. In the worst case, legionella can form. THPS is one of the most commonly used non-oxidising biocides to combat these problems.

Its effectiveness also depends on the correct dosage. With this Test Kit, you can quickly and easily monitor the use of THPS anywhere at any time.

Faixa de Medição

lest Name	Faixa de Medição
THPS	0 - 100 ppm

Texto do Escopo de Entrega

- Plastic case
- THPS Reagent 1
- THPS Reagent 2
- THPS Reagent 3
- Syringe plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Instruction manual

Título	Artigo No	
Seringa, plástico, 20 mL	56A00650	
Recipiente de titulação com tampa, plástico, 60 mL	56A006701	
Seringa de plástico 10 ml	56A008601	
Filtro Gf/C, 25 mm	56A019950	

Tintometer GmbH

Lovibond® Water Testing Schleefstraße 8-12 44287 Dortmund Tel.: +49 (0)231/94510-0 sales@lovibond.com www.lovibond.com Alemanha

Tintometer Brazil

Caixa Postal: 271 CEP: 13201-970 Jundiaí – SP Tel.: +55 (11) 3230-6410 sales@lovibond.us

www.lovibond.com.br

Brasil

The Tintometer Limited

Lovibond House Sun Rise Way Amesbury, SP4 7GR Tel.: +44 (0)1980 664800 sales@lovibond.uk www.lovibond.com Reino Unido

Tintometer Inc.

6456 Parkland Drive Sarasota, FL 34243 Tel: 941.756.6410 Fax: 941.727.9654 sales@lovibond.us www.lovibond.us EUA

Tintometer China 9F, SOHO II C. No.9 Guanghualu,

Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer India Pvt. Ltd.

Índia

Door No: 7-2-C-14, 2nd, 3nd & 4m Floor Sanathnagar Industrial Estate, Hyderabad, 500018 Telangana Tel: +91 (0) 40 23883300 Toll Free: 1 800 599 3891/ 3892 indiaoffice@lovibond.in www.lovibondwater.in

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard, Lebuh Nilam 2, Bandar Bukit Tinggi, Klang, 41200, Selangor D.E Tel.: +60 (0)3 3325 2285/6 Fax: +60 (0)3 3325 2287 lovibond.asia@tintometer.com www.lovibond.com Malásia

Tintometer Spain

Postbox: 24047 08080 Barcelona Tel.: +34 661 606 770 sales@tintometer.es www.lovibond.com Espanha

Technical changes without notice
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies