# Lovibond<sup>®</sup> Colour Measurement Tintometer<sup>®</sup> Group



# LC 100 Spectrocolorimeter

Hand-Held Imaging Spectrocolorimeter



## -- Hand-Held Imaging Spectrocolorimeter

- Versatile Communication of Color Measurement
- Single, Simple, Reliable, Integrated Tool -No Need to Connect to PC
- Readings and Comparison Charts within Seconds

Part Number: 401100

### Portable, Ergonomic & Extremely Versatile

The LC 100 gives you great flexibility in color measurement. It is a lightweight tool that is easy to handle and ready to use. In just over a second, it not only provides you a reading of the sample but also a report telling how close the color is to a measured standard. It is the ideal solution for the color measurement of many applications. The carrying pouch also means you can keep the instrument with you at all times, giving you immediate access to results.

### Easy, Instant Reporting to Share and Store Results

The LC 100 automatically creates conformance reports in either PDF or Excel formats for each stored sample against each standard. These can easily be shared with a PC or directly to a compatible printer (via USB mass storage mode).

#### Versatile Communication of Color Measurement

You can get results in just over a second and view them easily with: Graphical Pass/Fail indicator

Display of  $\Delta E$  for all common methods ie CIELAB, CMC, CIE 94, 2000 Display of measured and delta differences with L\*a\*b\*C\*h° for standard and sample Graphical L\*a\*b\* plot Verbal color difference description

# Single, Simple, Reliable, Integrated Tool - No Need to Connect to a PC

Utilizing the LC 100, you can ensure that all your staff are speaking the same language with an easy pass/fail measurement.

# Upgrade to the LC 100 / SV 100 to Measure Awkward Samples

The Lovibond<sup>®</sup> LC 100 and SV 100 integrated package provides a unique solution for you to measure food, powders, cosmetics and pastes. The SV 100 holder supports the LC 100 at an ergonomic viewing angle to enable the measurements in Lovibond® optical cells. A secure cap is provided to cover the sample, protecting it from any excessive ambient light, enabling quick yet accurate readings. The units are provided in a purpose-designed case containing all the accessories required for accurate color measurement expected of the Lovibond<sup>®</sup> brand.

#### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

#### Application

Chemicals | Coatings | Food and Beverage | Household Products | Medical and Clinical Products | Pharmaceuticals and Cosmetics | Plastics | Sugar Solutions, Syrups and Honey | Textiles

### LC 100 Spectrocolorimeter

A very easy to use, extremely portable instrument spectrocolorimeter for quick yet accurate reporting of any possible deviations of color against your defined color scale. Up to 350 sample measurements can be stored on the device and compared to reference standards.

#### **Technical Data**

| Applicable Standard         | ASTM E308                                    |
|-----------------------------|--|
| Color Type                  | Opaque                                       |
| Display                     | 4.5 cm Colour TFT                            |
| Interfaces                  | USB  |
| Measuring<br>Geometrics     | 45/0 Image Capture                           |
| Internal Storage            | 30 standards/350 sample results              |
| Measurement Time            | 1.8 seconds                                  |
| Storage Temperature         | -20° to 60°C (-4°F to 104°F)                 |
| Short Term<br>Repeatability | Typical 0.10 $\Delta$ E 94 on white (D65/10) |
| Illuminants                 | CIE Illuminant A<br>CIE Illuminant D65       |
| Portability                 | Portable                                     |

# **Delivery Scope**

— LC 100 Handheld Spectrocolorimeter

- Carrying Pouch

 UBS Cable for Power Supply and Data Transfer

#### Tintometer GmbH

Lovibond® Water Testing Schleefstraße 8-12 44287 Dortmund Tel.: +49 (0)231/94510-0 sales@lovibond.com www.lovibond.com Germany

#### Tintometer Brazil

Caixa Postal: 271 CEP: 13201-970 Jundiaí – SP Tel.: +55 (11) 3230-6410 sales@lovibond.us www.lovibond.com.br Brazil

#### The Tintometer Limited

Lovibond House Sun Rise Way Amesbury, SP4 7GR Tel.: +44 (0)1980 664800 sales@lovibond.uk www.lovibond.com UK

Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 Tel: 941.756.6410 Fax: 941.727.9654 sales@lovibond.us www.lovibond.us USA

#### **Tintometer China**

9F, SOHO II C. No.9 Guanghualu, Chaoyang District, Beijing, 100020 Customer Care China Tel.: 4009021628 Tel.: +86 10 85251111 Ext. 330 Fax: +86 10 85251001 chinaoffice@tintometer.com www.lovibond.com China

#### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>rd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor Sanathnagar Industrial Estate, Hyderabad, 500018 Telangana Tel: +91 (0) 40 23883300 Toll Free: 1 800 599 3891/ 3892 indiaoffice@lovibond.in www.lovibondwater.in India

#### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard, Lebuh Nilam 2, Bandar Bukit Tinggi, Klang, 41200, Selangor D.E Tel.: +60 (0)3 3325 2285/6 Fax: +60 (0)3 3325 2287 lovibond.asia@tintometer.com www.lovibond.com Malaysia

#### **Tintometer Spain**

Postbox: 24047 08080 Barcelona Tel.: +34 661 606 770 sales@tintometer.es www.lovibond.com Spain

Technical changes without notice

Printed in Germany Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies