

Lovibond® Water Testing

Tintometer® Group



MINIKIT AF 416, Calcium Hardness, 10-500 mg/L CaCO₃

Versatile rapid tests for a wide range of applications



- Easy operation and exact reagent dosing
- High accuracy
- Foil-wrapped Lovibond tablet reagents with a minimum guaranteed shelf life of 5 years
- Unrestricted shipment

Part Number: 414160

Various test procedures

For the Aqualytic® MINIKITs various test procedures are available: Choose between manual test procedures, Turbidity or Tablet Count Method or the so-called Speed test.

Intuitive application

Whether professional or layman: with the Aqualytic® MINIKIT everyone achieves error-free and reliable results.

Aqualytic® MINIKIT durability

The reagents used in the Aqualytic® MINIKITs have a shelf life of 5 years. And best of all - they are not subject to any transport restrictions.

Directly usable

In addition to the test kit in a sturdy plastic box, the delivery content also includes a measuring beaker, the necessary accessories and tablet reagents for approx. 30 tests.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Public | Pool Services | Power and Energy

MINIKIT AF 416, Calcium Hardness, 10-500 mg/L CaCO₃

They are user-friendly and suitable for a wide variety of applications in water analysis.

Thanks to various test procedures, the Aqualytic® MINIKITs are one thing above all else: a reliable companion.

Measuring Range

Test Name	Measuring Range
Hardness, calcium	10 - 500 mg/L CaCO ₃

Delivery Scope

- Kit in a plastic box
- Tablet reagents for an average of 30 tests
- Sample container
- Required accessories
- Instruction manual

Title	Part Number
Brush, 11 cm length	380230
Plastic shaker tube, graduated 100 ml, with lid	385130

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain