

Lovibond® Water Testing Tintometer® Group



MINIKIT AF 434, Sulfite, 2-50 mg/L Na₂SO₃

Titration Test Kit for Low Range Sulfite



- Tablet reagents extend shelf-life of test kits and make reagent dosing easy and precise
- Supplied ready-to-use with reagents and accessories
- Simple instructions, available in 8 languages

Part Number: 414340

Easy procedures with exact reagent dosing

Dispensing tablets is simple, precise, and safe. Simply push the foil through the pharmaceutical grade aluminum foil into the titration tube.

Intuitive procedures

MINIKITs are designed for use by professionals as well as non-technical users. Procedures are simple and easy to follow, ensuring everyone achieves error-free and reliable results.

Long shelf-life

Tablet reagents used in the MINIKITs have up to a 5-year shelf life. And best of all - they are not subject to any transport restrictions.

Supplied ready-to-use

All MINIKITs are supplied in a carrying case, making it easy to test in the field and keep supplies organized. Kits are supplied with the required accessories and tablet reagents.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Oil and Gas | Pharmaceutical Industry | Power and Energy

MINIKIT AF 434, Sulfite, 2-50 mg/L Na₂SO₃

The Low Range Sulfite MINIKIT is used to detect the level of sulfite in a water sample over the range of 2 - 50 mg/l sulfite as Na₂SO₃.

Lovibond® has replaced the liquid titration solution and indicator with tablet reagents - making reagent dosing simple, exact, and safe. With this test, tablets are added to a defined sample volume until a chemically induced color change takes place. The final result is calculated from the number of tablets required for the color change to occur.

Measuring Range

Test Name	Measuring Range
Sulphite, low	2 - 50 mg/L Na ₂ SO ₃

Delivery Scope

- Kit in a plastic box
- 20 x Sulfite No. 1 Tablets
- 100 x Sulfite LR No. 2 Tablets
- Plastic shaker tube, graduated 100 ml with lid
- Instruction manual

Title	Part Number
Brush, 11 cm length	380230
Plastic shaker tube, graduated 100 ml, with lid	385130

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain