


Lovibond® Water Testing Tintometer® Group



Scuba II

Test equipment for the responsible private swimming pool and whirlpool operator



- Modern, ergonomic design
- User friendly handling
- Watertight housing*
- Large display

Part Number: 216100-17

Main pool parameters

Whoever as a private pool owner value accurate measurement results of the important pool parameters, such as Chlorine or pH sets, gets with the Scuba II an ideal test device to the hand. The device works intuitively and measures the most important pool parameters of free chlorine, total chlorine, bromine, pH, alkalinity-m and cyanuric acid.

Waterproof

And if the device falls into the water? No problem - the Scuba II is not only waterproof but also buoyant.

Integrated measuring chamber

Take a sample by immersing the measuring chamber in the instrument.

Fast results

Add a reagent and press "Test" button. The result is available within a few seconds. Or in other words: measuring like the pros.

Industry

Pool Domestic | Pool Services

Application

Pool Water Control

Scuba II

Floatable, waterproof and certainly a useful little helper for the pool: The Scuba II is for private pool owners the ideal companion for the bathing season. Measure the most important parameters and hold the results in your hands immediately.

Measuring Range

Test Name	Measuring Range	Chemical Method
Alkalinity-m T	0 - 300 mg/L CaCO ₃	Acid / Indicator
Bromine T	0.2 - 13 mg/L Br ₂	DPD
Chlorine T	0.1 - 6.0 mg/L Cl ₂ ^{a)}	DPD
CyA T	1 - 160 mg/L CyA	Melamine
pH-value T	6.5 - 8.4 pH	Phenol Red

Technical Data

Optics	temperature-compensated LED ($\lambda = 530 \text{ nm}$) and photo-sensor
Operation	Foil keypad
Portability	Portable
Compliance	CE
Dimensions	2.76 x 1.77 x 5.71"

Delivery Scope

- Scuba II In plastic box
- 20 DPD No.1 tablet reagents
- 20 Phenol Red Photometer tablet reagents
- 10 DPD No.3 Evo tablet reagents
- 10 CyA-Test tablet reagents
- 10 Alka-M-Photometer tablet reagents
- Instruction manual
- 2 Batteries (AAA)
- Stirring rod

Title	Part Number
Battery lid for Scuba II	19801802-3
Rubber seal cap for Scuba	19802218
Stirring rod, blue, 10 cm	364107

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain