

# Lovibond® Water Testing Tintometer® Group



## MD 100 Chloride, tablet reagents

Precise Water Analysis in High-Quality Design



- Lightweight, rugged design for use in the field
- Single unit construction with no parts to lose or break
- Large, easy to read display
- Industry specific parameter combinations available

Part Number: 276180

The MD 100 has several key features that make it a favorite among users.

### Waterproof Design

The IP 68 design of this instrument ensures that the MD 100 remains water tight for up to 1 hour at 0.1 meter. Don't worry about dropping the instrument into a body of water - it floats!

### Accurate, Reproducible Results

The optical system of the MD 100 utilizes LEDs and interference filters which quickly gives you results that you can be confident in.

### User Calibration Mode

A one-point calibration is possible. Additionally, all MD 100 instruments have the ability to display readings directly in ABS or %T units.

### One-time-Zero Function

Don't waste time waiting for your instrument to Zero after each test. When testing a new sample, zero the instrument once and all subsequent tests of that sample do not require you to re-zero the instrument.

### Automatic Data Storage with Transfer Capabilities

The MD 100 automatically stores the last 16 readings with time and date stamp. These results can be transferred to a spreadsheet using the IRiM accessory.

### Ergonomic Design

Whether you're using the MD 100 out in the field or in the lab, the design of the instrument makes it easy to handle and view the display. If you're using the instrument in the lab, the rubber feet on

the bottom of the housing eliminates the need for two hand operation or to chase your instrument around the workbench.

### Factory Programmed

All MD 100 instruments are supplied ready to use with up to 14 calibration curves. All you need to do is select the test you need, prepare your sample and test!

### Scroll Driven Menu System

The simple interface allows you to quickly reach the test you need. When the instrument is turned on, it will automatically display the last test used.

### 2-Year Manufacturer's Warranty

## Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Power and Energy

## Application

Cooling Water | Drinking Water Treatment | Galvanization | Raw Water Treatment | Waste Water Treatment

## MD 100 Chloride, tablet reagents

The MD 100 photometer is a convenient choice for testing up to 14 parameters on a single instrument.

The instrument has a simple user interface and is constructed for field use. Several industry specific versions are available the combine all of the tests you need.

## Measuring Range

Test Name	Measuring Range	Chemical Method
Chloride T	0.5 - 25 mg/L Cl <sup>-</sup>	Silver Nitrate / Turbidity
Chloride T	5 - 250 mg/L Cl <sup>-</sup> <sup>9)</sup>	Silver Nitrate / Turbidity

## Technical Data

<b>Optics</b>	LEDs, interference filters (IF) and photo sensor in transparent sample chamber. Depending on the version, up to 3 different interference filters are used. Wavelength specifications of interference filters: 430 nm $\Delta\lambda = 5$ nm 530 nm $\Delta\lambda = 5$ nm 560 nm $\Delta\lambda = 5$ nm 580 nm $\Delta\lambda = 5$ nm 610 nm $\Delta\lambda = 6$ nm 660 nm $\Delta\lambda = 5$ nm
<b>Wavelength Accuracy</b>	± 1
<b>Photometric Range</b>	-2500 - 2500 mAbs
<b>Display</b>	backlit LCD (on keypress)
<b>Interfaces</b>	Infrared
<b>Operation</b>	Foil keypad
<b>Calibration</b>	factory calibration and user calibration. Reset to factory calibration possible
<b>Internal Storage</b>	internal ring memory for 16 data sets
<b>Battery Life Time</b>	approx. 17 hours
<b>Clock</b>	Real Time Clock and Date
<b>Portability</b>	Portable
<b>Compliance</b>	CE
<b>Dimensions</b>	6.1 x 2.95 x 1.38"

## Delivery Scope

- Instrument in plastic case
- 100 tablet reagents Chloride T1
- 100 tablet reagents Chloride T2
- 4 micro batteries (AAA)
- 3 round cuvettes (glass) with lid
- Sealing rings
- Stirring rod
- Brush
- Syringe (1 ml)
- Syringe (10 ml)
- Instruction manual
- Quick Start Guide
- Certificate (COC)
- Warranty information

Title	Part Number
Water sampler with bottle 250 mL and lid, AF 631	170500
Micro batteries (AAA), set of 4	1950026
Multy cuvette-2, set of 12	197600
Round cuvette 24 mm ø, set of 12	197620
Sealing ring for round vials 24 mm ø, set of 12	197626
Round cuvette 24 mm ø, set of 5	197629
Cleaning cloth	197635
Round cuvette 16 mm ø, set of 10	197665
Adapter for round cuvettes 16 mm ø	19802190
Mixing cylinder, 25 ml	19802650
Verification Standard Kit MD 100 / 200	215670
Stirring rod, 13 cm length	364100
Stirring rod, 10 cm length	364109
Stirring rod, 13 cm length, set of 10	364120
Stirring rod, 10 cm length, set of 10	364130
Pipette, 1000 µl	365045
Membrane filter set for use when preparing samples, 25 membrane filters 0.45 µm, 2 syringes 20 ml	366150
250 mL bottle, AF 631	375072
Brush, 11 cm length	380230
Measuring beaker, 100ml	384801
Cuvette stand for 6 round cuvettes Ø 24 mm	418951
Cuvette stand for 10 round cuvettes Ø 16 mm	418957
Pipette tips, 0,1-1 ml (blue), 1000 pc.	419073
Plastic funnel with handle (white)	471007
Additionally for each method	999855

---

**Tintometer GmbH**

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

**The Tintometer Limited**

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
UK

**Tintometer China**

9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Tintometer South East Asia**

Unit B-3-12, BBT One Boulevard,  
Lebu Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

**Tintometer Brazil**

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

**Tintometer Inc.**

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

**Tintometer India Pvt. Ltd.**

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain