

| Chlorine dioxide T | M120 |
|---------------------------------|------|
| 0.02 - 11 mg/L CIO ₂ | CLO2 |
| DPD / Glycine | |

Instrument specific information

The test can be performed on the following devices. In addition, the required cuvette and the absorption range of the photometer are indicated.

| Instrument Type | Cuvette | λ | Measuring Range |
|---|---------|--------|----------------------------------|
| MD 100, MD 110, MD 200, MD 600, MD 610, MD 640, MultiDirect, PM 620, PM 630 | ø 24 mm | 530 nm | 0.02 - 11 mg/L ClO ₂ |
| MD50 | ø 24 mm | 530 nm | 0.04 - 11 mg/L ClO ₂ |
| XD 7000, XD 7500 | ø 24 mm | 510 nm | 0.02 - 11 mg/L ClO ₂ |
| SpectroDirect | ø 24 mm | 510 nm | 0.05 - 2.5 mg/L CIO ₂ |



Chlorine dioxide T / M120

Material

Required material (partly optional):

| Reagents | Packaging Unit | Part Number |
|--|----------------|-------------|
| DPD No.1 | Tablet / 100 | 511050BT |
| DPD No. 1 | Tablet / 250 | 511051BT |
| DPD No. 1 | Tablet / 500 | 511052BT |
| DPD No. 3 | Tablet / 100 | 511080BT |
| DPD No. 3 | Tablet / 250 | 511081BT |
| DPD No. 3 | Tablet / 500 | 511082BT |
| Glycine ⁿ | Tablet / 100 | 512170BT |
| Glycine ⁿ | Tablet / 250 | 512171BT |
| DPD No. 3 High Calcium ^{e)} | Tablet / 100 | 515730BT |
| DPD No. 3 High Calcium ^{e)} | Tablet / 250 | 515731BT |
| DPD No. 3 High Calcium ^{e)} | Tablet / 500 | 515732BT |
| DPD No. 1 High Calcium ^{e)} | Tablet / 100 | 515740BT |
| DPD No. 1 High Calcium ^{e)} | Tablet / 250 | 515741BT |
| DPD No. 1 High Calcium ^{e)} | Tablet / 500 | 515742BT |
| Set DPD No. 1/No. 3 100 Pc.# | 100 each | 517711BT |
| Set DPD No. 1/No. 3 250 Pc.# | 250 each | 517712BT |
| Set DPD No. 1/Glycine 100 Stck. # | 100 each | 517731BT |
| Set DPD No. 1/Glycine 250 Stck. # | 250 each | 517732BT |
| Set DPD No. 1/No. 3 High Calcium 100 Pc. # | 100 each | 517781BT |
| Set DPD No. 1/No. 3 High Calcium 250 Pc. # | 250 each | 517782BT |
| DPD No. 3 Evo | Tablet / 100 | 511420BT |
| DPD No. 3 Evo | Tablet / 250 | 511421BT |
| DPD No. 3 Evo | Tablet / 500 | 511422BT |

Application List

- Waste Water Treatment
- Disinfection Control
- Boiler Water
- Cooling Water
- Raw Water Treatment
- Pool Water Control
- Drinking Water Treatment



Sampling

- 1. When preparing the sample, outgassing, e.g. through the pipette or shaking, must be avoided.
- 2. The analysis must take place immediately after taking the sample.

Preparation

1. Cleaning of vials:

As many household cleaners (e.g. dishwasher detergent) contain reducing substances, this can lead to lower results with the determination of Chlorine dioxide. To avoid measurement errors, the glassware used should be free of chlorine consumption. To achieve this, all glassware should be placed in a sodium hypochlorite solution (0.1 g/L) for one hour and then rinsed thoroughly with deionised water.

2. Strong alkaline or acidic water samples must be adjusted between pH 6 and pH 7 before the analysis (use 0.5 mol/l Sulphuric acid or 1 mol/l Sodium hydroxide).

Notes

1. EVO tablets can be used as an alternative to the corresponding standard tablet (e.g. DPD No. 3 EVO instead of DPD No. 3).



Chlorine dioxide T / M120



Determination of Chlorine Dioxide, in absence of chlorine with tablet

Select the method on the device.

In addition, choose the test: without Chlorine

For this method, a ZERO measurement does not have to be carried out every time on the following devices: XD 7000, XD 7500







Fill 24 mm vial with 10 mL Close vial(s). sample.

Place sample vial in the sample chamber. Pay attention to the positioning.



Press the ZERO button.



Empty vial except for a few



Add DPD No.1 tablet .



drops. For devices that require no ZERO measurement, start here.



Crush tablet(s) by rotating slightly.



Fill up vial with sample to the 10 mL mark.





Close vial(s).



Dissolve tablet(s) by inverting.



Place **sample vial** in the sample chamber. Pay attention to the positioning.



Press the **TEST** (XD: **START**)button.

The result in mg/L Chlorine Dioxide appears on the display.



Determination of Chlorine Dioxide, in presence of chlorine with tablet

Select the method on the device.

In addition, choose the test: in presence of Chlorine

For this method, a ZERO measurement does not have to be carried out every time on the following devices: XD 7000, XD 7500







Fill 24 mm vial with 10 mL Add GLYCINE tablet. sample.



Close vial(s).



Close vial(s).



Dissolve tablet(s) by inverting.



Place sample vial in the sample chamber. Pay attention to the positioning.

Crush tablet(s) by rotating



Fill a second vial with 10 mL sample .



Press the ZERO button.

slightly.

EN Method Reference Book 1.0



Chlorine dioxide T / M120





Remove the vial from the sample chamber.

Empty vial.

For devices that require no ZERO measurement , start here.





Crush tablet(s) by rotating slightly.



Fill prepared vial with prepared **glycine solution**.



Close vial(s).



Dissolve tablet(s) by inverting.



Place **sample vial** in the sample chamber. Pay attention to the positioning.







Remove the vial from the sample chamber.



Thoroughly clean the vial and vial cap.



Press the TEST (XD:

START)button.





Fill vial with some drops of Add DPD No. 1 tablet . sample.



Fill up vial with sample to the 10 mL mark.



Test

Close vial(s).

Crush tablet(s) by rotating slightly.



Dissolve tablet(s) by inverting.



Remove the vial from the sample chamber.



Place sample vial in the sample chamber. Pay attention to the positioning.

Press the TEST (XD: START)button.







Add DPD No.3 tablet .



Crush tablet(s) by rotating slightly.



Close vial(s).



Dissolve tablet(s) by inverting.





Place **sample vial** in the sample chamber. Pay attention to the positioning.

Press the **TEST** (XD: **START**)button.



Wait for 2 minute(s) reaction time.

Once the reaction period is finished, the measurement takes place automatically.

The result in mg/L Chlorine Dioxide appears on the display.



Analyses

The following table identifies the output values can be converted into other citation forms.

| Unit | Cite form | Scale Factor |
|------|----------------------|--------------|
| mg/l | CIO ₂ | 1 |
| mg/l | Cl ₂ frei | 0.525 |
| mg/l | Cl ₂ geb. | 0.525 |
| mg/l | ges. Cl ₂ | 0.525 |

Chemical Method

DPD / Glycine

Appendix

Calibration function for 3rd-party photometers

Conc. = $a + b \cdot Abs + c \cdot Abs^2 + d \cdot Abs^3 + e \cdot Abs^4 + f \cdot Abs^5$

| | ø 24 mm | □ 10 mm |
|---|-----------------------------|-----------------------------|
| а | -8.24762 • 10 ⁻² | -8.24762 • 10 ⁻² |
| b | 3.33567 • 10 ⁺⁰ | 7.17169 • 10 ⁺⁰ |
| С | -1.16192 • 10 ⁻¹ | -5.37098 • 10 ⁻¹ |
| d | 1.95263 • 10 ⁻¹ | 1.9406 • 10 ⁺⁰ |
| е | | |
| f | | |

Interferences

Persistant Interferences

1. All oxidising agents in the samples lead to higher results.

Removeable Interferences

 Concentrations above 19 mg/L chlorine dioxide can lead to results within the measuring range of up to 0 mg/L. In this case, the water sample must be diluted with water that is free from chlorine dioxide. 10 ml of the diluted sample should be mixed with the reagent and the measurement taken again.

Derived from

DIN 38408, Section 5



^{a)} alternative reagent, used instead of DPD No.1/No.3 in case of turbidity in the water sample caused by high concentration of calcium and/or high conductivity | ^a additionally required for determination of bromine, chlorine dioxide and ozone in the presence of chlorine | [#] including stirring rod, 10 cm