

# Lovibond® Water Testing

## Tintometer® Group



### SD 315 Oxi (Set 1)

Waterproof Hand-held Meters for the determination of Dissolved oxygen (O<sub>2</sub>)/O<sub>2</sub> -Concentration/O<sub>2</sub> -Saturation Temperature



- Rugged, water resistant (IP 67)
- PC interface (USB / serial or analog)
- Automatic buffer detection (SD 300 pH)
- Data logger and alarm function (min./ max.)

Part Number: 724680

#### No polarization

The well-known Clark oxygen sensor allows immediate measurement without polarization time.

#### Versatile

The SD 315 Oxi is aimed at industry, laboratories and urban facilities, such as sewage treatment or water works.

#### Data management

A data logger and the corresponding logger software ensure simplified processing of the data obtained.

To ensure that this works under all visual conditions, the device is delivered with a backlit display.

#### housing

The protective armor not only guarantees a secure grip but also protection against fall damage.

The stand attached to the back of the housing can also be used as a hanger or belt clip.

#### Alarm

The integrated alarm alerts you if the measured value deviates once from the predefined values.

#### Auto-Hold

The auto-hold function makes it easy to read the measured values.

#### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Power and Energy

#### SD 315 Oxi (Set 1)

Portable handheld instrument for the determination of dissolved oxygen. It's reliable, rugged, and ideal for instant measurements with no time-consuming polarization time, thanks to the Clark oxygen sensor.

#### Measuring Range

Test Name	Measuring Range
Oxygen	0 - 70 mg/L O <sub>2</sub>
Oxygen	0 - 600 %
Temperature	0 - 50 °C

## Technical Data

<b>Display</b>	Backlit LCD
<b>Data Logger</b>	Manual Logger: 1000 data sets (single value by key-stroke). Auto. Logger: 10000 data sets (cyclic, time interval: 1 - 3600 s)
<b>Auto – OFF</b>	Yes
<b>Power Supply</b>	2 AAA batteries Micro-USB
<b>Portability</b>	Portable
<b>Temperature Compensation</b>	yes
<b>Protection Class</b>	IP 67
<b>Compliance</b>	CE
<b>Languages User Interface</b>	German, English, French, Spanish, Italian, Portuguese, Dutch, Chinese
<b>Dimensions</b>	98 x 37 x 164 mm
<b>Weight</b>	287 g

Title	Part Number
KOH 100, Spare Electrolyte, 100 ml for SD 310 / SD 315 Oxi	19801130
Oxygen sensor for SD 310 / SD 315 Oxi with 2 m cable, Platinum cathode / Lead anode	19805050
Oxygen sensor for SD 310 / SD 315 Oxi with 10 m cable, Platinum cathode / Lead anode	19805051
Oxygen sensor for SD 310 / SD 315 Oxi with 30 m cable, Platinum cathode / Lead anode	19805052
Protection cap for Oxygen sensor SD 310 / SD 315 Oxi for depth measurement (PVC)	19805055
Protection cap for Oxygen sensor SD 310 / SD 315 Oxi for depth measurement (brass)	19805056
Bottle for storage and calibration	19805057
USB cable, for connection to a computer for SD 300 / SD 305	724620
GSOFT 3050 Windows-Software with logger for SD 300 / SD 305 series	724625
Service Set for Oxygen sensor SD 300 / SD 315 Oxi consisting of 3 pcs. Spare Membrane Heads and 100 ml KOH (1.18 mol/l) Elektrolyt solution	724670
Case incl. foam for SD 305 series	725070

## Delivery Scope

- Instrument in protective armoring including electrode holder
- Batteries
- Oxygen sensor with 2 m cable
- Electrolyte solution (KOH) 100 ml
- Calibration bottle with sponge
- 2 pcs. spare membrane heads
- Instruction manual
- Warranty information

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
UK

### Tintometer China

9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain