

# Lovibond® Water Testing Tintometer® Group



## SD 305 pH/ORP (Set 3)

Waterproof Hand-held Meters for the determination of pH/Redox/Temperature



- Rugged, water resistant (IP 67)
- PC interface (USB / serial or analog)
- Automatic buffer detection
- Data logger and alarm function (min./max.)

Part Number: 724642

### Technically advanced

A particularly high resolution (0.001 pH / 0.1 mV) for maximum accuracy, automatic temperature compensation and buffer detection are further features of the SD 305 pH/ORP.

### User-friendly Handling

The comfortable handling is completed by a large, backlit display. So you have the measurement results directly in view in every situation.

### Data management

Data collected by the data logger can be transferred to the computer via USB interface (serial or analogue).

### Housing

The protective reinforcement not only guarantees safe working at all times, even in extreme environmental conditions. The stand attached to the back of the housing can also be used as a hanger or belt clip.

### Additional equipment

Battery and electrode status indication, battery replacement indicator, auto-off, auto-hold, min./max. Value memory are also included as functions.

### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Power and Energy

### Application

Boiler Water | Cooling Water | Drinking Water Treatment | Pool Water-Control | Waste Water Treatment

### SD 305 pH/ORP (Set 3)

Portable handheld instrument for the determination of pH values. It is reliable, waterproof (IP67) and robust, making it an ideal solution for on-site analysis.

#### Note according to EU regulation 2019/1148

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. See [https://ec.europa.eu/info/index\\_en](https://ec.europa.eu/info/index_en)

### Measuring Range

Test Name	Measuring Range
pH	-2 - 16
Redox	-1999.9 - 1999.9 mV
Temperature	-5 - 150 °C

## Technical Data

<b>Display</b>	Backlit LCD
<b>Interfaces</b>	USB
<b>Data Logger</b>	Manual Logger: 1000 data sets (single value by key-stroke). Auto. Logger: 10000 data sets (cyclic, time interval: 1 - 3600 s)
<b>Auto – OFF</b>	Yes
<b>Calibration</b>	automatic or manual 1-, 2, or 3-point calibration
<b>Power Supply</b>	2 AAA batteries Micro-USB
<b>Battery Life Time</b>	500 h
<b>Portability</b>	Portable
<b>Temperature Compensation</b>	Automatic
<b>Protection Class</b>	IP 67
<b>Compliance</b>	CE
<b>Languages User Interface</b>	German, English, French, Spanish, Italian, Portuguese, Dutch, Chinese
<b>Dimensions</b>	128 x 164 x 37 mm
<b>Weight</b>	287 g

## Title

## Part Number

GSOFT 3050 Windows-Software with logger for SD 300 / SD 305 series	724625
Case incl. foam for SD 305 series	725070
3 M KCl Storage Solution for pH/ORP, 25 ml	726402
3 M KCl Storage Solution for pH/ORP, 100 ml	726404

## Delivery Scope

- Instrument in protective armoring including electrode holder
- Redox electrode, plastic/gel, type 242, BNC-plug (order code 721242BNC)
- Temperature sensor PT 1000 (order code 721245)
- Redox Standard Solution 470 mV
- Storage Solution for pH/ORP
- Batteries
- Instruction Manual
- Warranty information
- in case

Title	Part Number
Redox calibration solution, 470 mV, 100 ml	195070
pH electrode, plastic/gel, type 226, without temperature sensor, BNC-plug	721226
pH/temp. electrode, type 231, plastic/gel/temp. NTC30kOhm, BNC-plug for SD 300 / SD 305 pH (SET 1)	721231
pH electrode glass/gel, type 235, without temperature sensor, BNC-plug forSD 300 / SD 305 pH	721235BNC
Redox electrode, plastic/gel, BNC-plug, approx. 1 m cable	721242
Pt 1000, temperature sensor, metal, diameter 3 mm (SET 2)	721246
pH Buffer solution 4,01 (25 °C) red, 90 ml traceable to N.I.S.T	721247
pH-Buffer solution 7,00 (25 °C) yellow, 90 ml traceable to N.I.S.T.	721248
pH-Buffer solution 10,01 (25 °C) blue, 90 ml traceable to N.I.S.T.	721249
pH-Buffer solution Set pH 4, pH 7, pH 10 (25 °C), 90 ml	721250
pH Buffer solution 4,01 (25 °C) red, 1 ltr.traceable to N.I.S.T	721252
pH-Buffer solution 7,00 (25 °C) yellow, 1 ltr. traceable to N.I.S.T.	721254
pH-Buffer solution 10,01 (25 °C) blue, 1 ltr. traceable to N.I.S.T	721256
USB cable, for connection to a computer for SD 300 / SD 305	724620

---

**Tintometer GmbH**

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

**The Tintometer Limited**

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
UK

**Tintometer China**

9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Tintometer South East Asia**

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

**Tintometer Brazil**

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

**Tintometer Inc.**

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

**Tintometer India Pvt. Ltd.**

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain