

Lovibond® Water Testing Tintometer® Group



Cutting Fluid Test Kit

For the optimal effectiveness of cutting fluids



- Ensures compliance to regional Health and Safety at Work Procedures
- Optimises cutting fluid performance
- Safely controls microbiological contamination
- Optimised for accurate trend analysis

Code: 56K701180

Cutting fluids are required in metal machining to improve tool life, reduce work piece thermal deformation, enhance surface finish and to flush chips from the cutting zone. These fluids degrade with time due to bacterial growth and contamination with tramp oil.

Testing is essential since health risks exist for lathe operators by both fluid contact (dermatitis) and breathing of the mist/vapour (asthma, extrinsic allergic alveolitis and other breathing problems).

Biocidal additives improve the life of the fluid and reduce the hazard to health. On-going monitoring, inspection and maintenance are required in the UK as part of an employer's obligation under Section 2 of the Health and Safety at Work Act 1974. Similar work related mandates are in force across Europe.

Lovibond® test kits measure the key parameters necessary to optimise cutting fluid performance and enable enumeration and safe control of microbiological contamination. The basic kit is supplied with tests for cutting fluid concentration (refractometer), pH, water hardness, Nitrite/Nitrate and dipslides for monitoring microbiological activity. A deluxe version, incorporating the DI 10 dipslide incubator is also available. A uniform incubation temperature for dipslides allows accurate microbiological trend analysis month on month.

Industrie

Autres industries

Applications

Contrôle de la désinfection | Eau de refroidissement

Gamme de mesure

Test Name	Gamme de mesure
Comptage total / Levures et moisissures	
Glycol	% PEG/MEG
Nitrate/Nitrite	1 - 80 mg/L NO ₂ ⁻
pH	0 - 14
pH	7 - 14 pH

Contenu de livraison

- Plastic case
- SD40 Multi Pocket Tester
- Syringe plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Glycol Refractometer
- D003 TTC/RBS Dipslides (Rose Bengal)
- pH Buffer 4
- pH Buffer 7
- pH Buffer 10
- pH Test Strips, pH 7-14, plastic
- Nitrate/Nitrite Test Strips, 10-500/1-80 mg/L
- Instruction manual

Titre	Code
Seringue, plastique, 20 mL	56A006501
Réceptier de titrage avec couvercle, plastique, 60 mL	56A006701
D003 TTC/RBS Dipslides (rose bengale)	56B010310
Solution tampon KS3-pH 10 65 ml	56L000365
Solution tampon KS6-pH 4 65 ml	56L000665
Solution tampon KS9-pH 7 65 ml	56L000965

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Allemagne

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
Royaume-Uni

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
Chine

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaisie

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brésil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
États-Unis

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
Inde

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Espagne