

Lovibond® Colour Measurement Tintometer® Group



TA 4 Online-System

Continuous, Online Colour Measurement for Precise Process Control



- Continuous, online colour measurement for precise process control
- Flexibility through full range of industry-standard colour scales
- Seamless integration into production process - correlation with other instruments
- Eliminates time-loss and cost for sampling and lab measurements

Part Number: 178109

Seamless Integration into Production Process - Correlation with Other Instruments

The Lovibond® TA 4 online system enables you to instantly monitor colour quality throughout the manufacturing process. It is designed to be an easy-to-use monitoring system with the accuracy guaranteed of the Lovibond® brand.

Eliminates Time-loss and Cost for Sampling and Lab Measurements

The online system provides objective colour data for continuous process control, allowing near real-time process information to be obtained at a low analytical cost. The system can be used for the measurement of constituent concentrations, early detection of trace contaminants and quality assurance analysis. Analytical results can be fed back for automatic process control and optimisation.

Be Compliant to Internationally Recognised Colour Coordinate Systems

This new generation of online colorimeters utilise diode array spectrophotometers which measure a near real-time response across the spectrum (380 to 780 nm) at 10 nm or less. This spectrophotometric approach allows for the use of internationally recognised colour coordinate systems, such as CIELAB and CIE xzY with the subsequent translation of colour data to industry specific colour scales, as referenced by standardising bodies such as AOCS, DGF, ISO and ASTM.

Enjoy Ease-of-Use with Touch Screen Input and Display of Graphs

The interactive setup screen allows you to program details of both the reference spectrophotometer and those of the three flow cells. Once in deployment, the display can be set to show different measuring

points and the output scale can be selected. You can view the colour scales in two formats: either as a real-time graph for a single scale at a chosen measurement point or as a set of the latest values for all the scales at all the measurement points.

Facilitates Multiple Measurement Locations Throughout The Plant

The assembly consists of a Central Control Unit with a reference spectrophotometer. The Control Unit can accept signals from up to 3 flow cells to each of which up to 4 remote signals eg red, yellow, chlorophyll and CIELAB L* can be connected. The Central Control unit may be housed in a central location up to 45 m away from each cell.

There is no limit as to how many configurations you may install in the plant but each Central Control Unit runs independently and must be monitored separately.

Get Started with the Lovibond® Team

A team of Lovibond® trained engineers is on-hand to help you get started. With the company's in-depth knowledge of colour science, we can provide advice from colour scales, through recommended path lengths to implementation 'best practice'.

We can also arrange on-site visits to the factory plant for both pre- and post technical meetings, highlighting areas of consideration, advising on implementation and seeing the process through to completion.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

Application

Chemicals | Edible Oils and Fats

TA 4 Online-System

This generation of online colorimeters measures a near real-time response across the spectrum (380 to 780 nm) or less. This spectrophotometric approach allows for the use of internationally recognised colour coordinate systems, such as CIELAB and CIE xzY with the subsequent translation of colour data to industry specific colour scales, as referenced by standardising bodies such as AOCS, DGF, ISO and ASTM.

Technical Data

Applicable Standard	AOCS Cc 8d-55 AOCS Cc 13a-43 AOCS Cc 13b-45 AOCS Cc 13e-92 AOCS Cc 13j-97 ASTM D1209 ASTM D1544 ASTM D6166 ASTM E308 BS684 ISO 6271 ISO 15305 ISO 27608 MS 252 : Part 16 MS 817 : Part 12
Colour Type	Transparent
Display	Embedded PC with touch screen display, internal hard drive Windows XP operatin system
Path Length	1 inch, 50 mm, 5 1/4 inch
Calibration	Calibration loop filled with food grade glycerol, automatic calibration program included with software
Internal Storage	100,000+ Measurement
Measurement Time	Less than 5 seconds (depending on length of fiber optic cable)
Instrument Housing	Metal cabinet to IP66
Spectral Range	320 - 780 nm
Illuminants	CIE Illuminant A
Portability	Process
Observer	2°, 10°
Dimensions	500 x 500 x 300 mm

Delivery Scope

Please contact your local Lovibond® representative for details.

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain