

Lovibond® Water Testing Tintometer® Group



Scuba3s HR

Testeur de piscine électronique intelligent pour un contrôle exigeant de la piscine et du spa



- Transmission de données sans fil via NFC
- L'App PoolAssistant de Lovibond® pour l'entretien de la piscine & les résultats de mesure
- tous les paramètres importants de la piscine
- signal lumineux (vert/rouge) pour indiquer des conditions d'eau sûres

Code: 216210

NFC: Data transmission via chip

The passive NFC chip The passive NFC chip in the Scuba3s ensures wireless data transfer to an external device with an active NFC reader (e.g. smartphone). It works like putting on your EC card when shopping:

Simply hold the mobile phone close to the Scuba3s - and everything is on the device. All data records are transferred simultaneously and are immediately available in the Scuba app for evaluation. A data set includes the serial number and firmware version of the device, the name and number of the method, the dates and time of the measurement, the results and the units. A cloud is also available for data storage.

The PoolAssistant app: Quick overview always & everywhere

The PoolAssistant app helps you to evaluate the measurement results. After transfer via NFC, up to 3 users can immediately call up the data for each control parameter for a maximum of 5 pools. The app also classifies the results as diagrams for you and gives you tools for the right pool care, the appropriate chemistry and water quality. In the FAQ section, all important questions about pool water care, water hygiene or Langelier index are answered. You can also get valuable tips here.

Light signals for instant certainty

The light signals in the Scuba3s immediately show via the coloured backlight of the display whether the measurement result "fits" or not. If the light is green, the measurement result is within the ideal measuring range and you can start having fun in the pool. If the light is red, caution is advised: The measurement result is above or below the globally accepted measurement range for safe swimming. Also when evaluating data with the PoolAssistant app, the results are classified

with green and red signal colours. The app also helps you to find the cause.

More control parameters

With 5 parameters, the Scuba3s offers even more possibilities to control the water quality in the pool based on the most important ingredients. For this purpose, 3 measuring methods are available in the method list with just a few button presses: Chlorine (total, free, bound), alkalinity-m and urea provide information on whether the water quality in the pool is correct. The measuring process is now even faster.

New design, more functionality

Its ergonomic design remains: The Scuba3s also fits comfortably in one hand. The back is flattened so that it cuts a good figure everywhere. With the screwable battery compartment, the electronic pool tester is guaranteed waterproof and joins in every pool fun with reliable results. With 4 multifunction buttons, you can easily find your way around the user menu on the larger display accompanied by intuitive animations and icons.

Industrie

Piscines domestiques | Services autour des piscines

Applications

Contrôle de l'eau de la piscine

Scuba3s HR

Le Scuba ne manque à aucune piscine dans le monde. Avec la nouvelle génération du testeur de piscine électronique très apprécié, la surveillance de l'hygiène de la piscine est désormais encore plus rapide, plus polyvalente, plus maniable et plus simple. Gestion mobile des analyses incluse !

Gamme de mesure

Test Name	Gamme de mesure	Méthode chimique
Alcalinité-m HR T	50 - 500 mg/L CaCO ₃	Acide / Indicateur
Brome T	0.2 - 22.5 mg/L Br ₂	DPD
Chlorine HR T	0.2 - 10.0 mg/L Cl ₂ ^{a)}	DPD
Cuivre T	0.1 - 5 mg/L Cu ^{a)}	Biquinoline
CyA T	20 - 120 mg/L CyA	Mélamine
Dureté Calcium (B) T	50 - 500 mg/L CaCO ₃	Murexide
Phosphate LR T	0.06 - 3.0 mg/L PO ₄	Bleu phosphomolybdique
Urée T	0.2 - 5.0 mg/L Urea	Indophénol / Uréase
Valeur du pH T	6.5 - 8.4 pH	Rouge de phénol

Fiche technique

Optique	White LED, multichannel optical sensor with diffusor.
Display	LCD
Interfaces	NFC (Near Field Communication)
Fonctionnement	Clavier tactile
Auto – OFF	oui
Stockage interne	100 data sets
Alimentation	2 batteries (AA)
Durée de vie batterie	env. 90 mesures
Portabilité	Portable
Degré de pollution	2
Altitude maximale au-dessus du niveau de la mer	3500 m
Conditions environnementales	5 - 40 °C à une humidité relative de 30-90 % (sans condensation)
Classe de protection	IPX7 - Protégé contre les effets d'une immersion temporaire dans l'eau conformément à la norme DIN EN 60529
Conformité	CE UKCA
Dimensions	70 x 45 x 145 mm
Poids avec emballage	165 g

Contenu de livraison

- Scuba3s In plastic box
- 20 DPD No.1 HR tablet reagents
- 20 Phenol Red Photometer tablet reagents
- 10 DPD No.3 HR Evo tablet reagents
- 10 CyA-Test tablet reagents
- 10 Alka-M-HR Photometer tablet reagents
- 10 Calcio-H No.1 tablet reagents
- 10 Calcio-H No.2 tablet reagents
- Instruction manual
- 2 Batteries (AA)
- blue lid
- Stirring rod

Titre	Code
Capuchon en plastique souple Scuba	19802218
Agitateur en plastique, bleu, 10 cm	364107
ValidCheck Chlore 1,5 mg/l	48105510

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Allemagne

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Royaume-Uni

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
Chine

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaisie

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brésil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
États-Unis

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
Inde

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Espagne