

# Lovibond® Water Testing

## Tintometer® Group



## Cutting Fluid Test Kit

For the optimal effectiveness of cutting fluids



Cutting fluids are required in metal machining to improve tool life, reduce work piece thermal deformation, enhance surface finish and to flush chips from the cutting zone. These fluids degrade with time due to bacterial growth and contamination with tramp oil.

Testing is essential since health risks exist for lathe operators by both fluid contact (dermatitis) and breathing of the mist/vapour (asthma, extrinsic allergic alveolitis and other breathing problems).

Biocidal additives improve the life of the fluid and reduce the hazard to health. On-going monitoring, inspection and maintenance are required in the UK as part of an employer's obligation under Section 2 of the Health and Safety at Work Act 1974. Similar work related mandates are in force across Europe.

Lovibond® test kits measure the key parameters necessary to optimise cutting fluid performance and enable enumeration and safe control of microbiological contamination. The basic kit is supplied with tests for cutting fluid concentration (refractometer), pH, water hardness, Nitrite/Nitrate and dipslides for monitoring microbiological activity. A deluxe version, incorporating the DI 10 dipslide incubator is also available. A uniform incubation temperature for dipslides allows accurate microbiological trend analysis month on month.

- Ensures compliance to regional Health and Safety at Work Procedures
- Optimises cutting fluid performance
- Safely controls microbiological contamination
- Optimised for accurate trend analysis

Bestelnr.: 56K701180

### Industrie

Overige industrieën

### Applikation

Controle desinfecteermiddel | Koelwater

### Meetbereik

| Test Name                        | Meetbereik                               |
|----------------------------------|--|
| Glycol                           | % PEG/MEG                                |
| Nitrate/Nitrite                  | 1 - 80 mg/L NO <sub>2</sub> <sup>-</sup> |
| pH                               | 0 - 14                                   |
| pH                               | 7 - 14 pH                                |
| Totaal aantal / Gist & Schimmels |  |

# Leveromvang

- Plastic case
- SD40 Multi Pocket Tester
- Syringe plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Glycol Refractometer
- D003 TTC/RBS Dipslides (Rose Bengal)
- pH Buffer 4
- pH Buffer 7
- pH Buffer 10
- pH Test Strips, pH 7-14, plastic
- Nitrate/Nitrite Test Strips, 10-500/1-80 mg/L
- Instruction manual

| Omschrijving                             | Bestelnr. |
|--|-----------|
| Spuit, plastic, 20 mL                    | 56A006501 |
| Titratievat met deksel, kunststof, 60 mL | 56A006701 |
| D003 TTC/RBS Dipslides (Rose Bengal)     | 56B010310 |
| KS3-pH 10 bufferoplossing 65 ml          | 56L000365 |
| KS6-pH 4 bufferoplossing 65 ml           | 56L000665 |
| KS9-pH 7 bufferoplossing 65 ml           | 56L000965 |

**Tintometer GmbH**  
Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Duitsland

**The Tintometer Limited**  
Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
Verenigd Koninkrijk

**Tintometer China**  
9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Tintometer South East Asia**  
Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Maleisië

**Tintometer Brazil**  
Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazilië

**Tintometer Inc.**  
6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
Verenigde Staten

**Tintometer India Pvt. Ltd.**  
Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**  
Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spanje