

Lovibond® Water Testing Tintometer® Group



Water Treatment Engineers Test Kit (Photometer)

Test Kit for professionals for water treatment with photometric focus



You need safe, fast and reliable test results? This Kit allows you to test your water system in your daily routine with visual methods, electrochemical instruments and additionally with an MD600 photometer for advanced water analysis. This gives you the full overview and enables you to make the appropriate decisions on treatment programs.

Includes the following parameters: Conductivity, pH, glycol, aluminium, bromine, chlorine, copper, iron, molybdate and phosphate.

- Mobile laboratory for water treatment monitoring
- Accurate & repeatable results for all types of industrial water systems
- Including photometer MD600 for professional photometric tests
- Ensure system performance & operating costs

Bestelnr.: 56K701400

Industrie

Chemische industrie | Energieleveranciers | Farmaceutische industrie | Gemeenten | Ngo | Olie-industrie | Openbaar zwembad | Overige industrieën | Privézwembad | Scheepvaart | Voedingsmiddelen- en drankenindustrie | Zwembadservice

Applikation

Afvalwaterzuivering | Behandeling drinkwater | Controle desinfectiemiddel | Controle zwembadwater | Galvanisering | Ketelwater | Koelwater | Others | Zuivering vervuild water

Water Treatment Engineers Test Kit (Photometer)

The complete equipment for monitoring of closed circuits, evaporative cooling systems & boiler systems as routine tasks.

Ideal for prevention of most common problems and risks like corrosion, scale and biofouling or increased biological activity. The kit additionally contains an MD600 Photometer for professional photometric water sample analysis.

Meetbereik

Test Name	Meetbereik	Chemische methode
Alkalinity (P, M, OH)	50 - 2400 mg/L CaCO ₃	
Aluminium T	0.01 - 0.3 mg/L Al	Eriochromocyanine R
Broom T	0.05 - 13 mg/L Br ₂	DPD
Chloor T	0.01 - 6.0 mg/L Cl ₂ ^{a)}	DPD
Chloride	20 - 12000 mg/L Cl ⁻	
Conductivity	0 - 20 mS/cm	
Fosfaat HR T	0.33 - 26 mg/L P	Vanadomolybdaat
Glycol	% PEG/MEG	
Hardheid, totaal	5 - 600 mg/L CaCO ₃	
Hardheid (Ja/Nee)	8 - 20 mg/L CaCO ₃	
Hardness Calcium	5 - 600 mg/L CaCO ₃	
Hydrogen Peroxide	15 - 500 mg/L H ₂ O ₂	
IJzer HR L	0.1 - 10 mg/L Fe	Thioglycoleren
IJzer LR L (A)	0.03 - 2 mg/L Fe	Ferrozine / Thioglycolaat
Koper T	0.05 - 5 mg/L Cu ^{a)}	Biquinoline
Molybdaat T	1 - 50 mg/L MoO ₄	Thioglycoleren
Nitriet	10 - 2000 mg/L NaNO ₂	
pH	0 - 14	
Phosphonate	0 - 20 mg/L HEDP	
Sulphite	25 - 150 mg/L Na ₂ SO ₃	
Tannin	50 - 300 mg/L Tannin	

Leveromvang

- Plastic case
- SD40 Multi Pocket Tester
- MD610 Photometer
- 6 Cuvettes 24 mm round with lids & sealing rings
- DPD No.1 tablets BT
- DPD No.3 tablets
- Glycine tablets
- Nitrite tablets bottle
- Aluminium No.1 tablets
- Aluminium No.2 tablets
- Copper No.1 Test tablets
- Copper No.2 Test tablets
- Molybdate No.1 tablets
- Molybdate No.2 tablets
- Phosphate HR P1 tablets
- Phosphate HR P2 tablets
- Hardness Yes/No tablets
- Stirring rod and powder spoon
- pH Buffer 4 solution
- pH Buffer 7 solution
- pH Buffer 10 solution
- Chloride LR Titrant CC2
- Chloride HR Titrant BC2
- Tannin Indicator TN1
- Tannin Titrant TN2
- Acetic acid 20%
- Nitrite Titrant N2
- Phosphonate Titrant P5
- Peroxyacetic acid Buffer HP1
- Phosphonate Indicator P4L
- Nitrite Indicator N1
- Hydrogen Peroxide HR Titrant HP2
- Hydrogen Peroxide HR Titrant HP3
- Iron Reagent FE8
- Phosphonate pH Adjuster P3
- Chloride Indicator CC1
- Calcium Hardness Indicator CH1P
- Calcium Hardness Buffer CH2
- Phosphonate Neutraliser P1/2
- Sulphite Indicator S1
- Sulphite Titrant S2
- Alkalinity 4.5 Indicator TA4
- Alkalinity LR Titrant TA3
- Alkalinity HR Titrant PA2/TA2
- Alkalinity OH Reagent PA3
- Acidity/Alkalinity P Indicator PA1
- Hardness Total Buffer TH2
- Hardness Total Indicator TH1P
- Hardness LR Titrant TH3
- Hardness HR Titrant TH4
- 1413uS Standard Conductivity Solution
- Iron Reagent FE6
- Iron Reagent FE5

Omschrijving	Bestelnr.
ValidCheck Chloor 1,5 mg/l	48105510
Spuit, plastic, 20 mL	56A006501
Titratievat met deksel, kunststof, 60 mL	56A006701
Plastic spuit, 5 mL	56A008501
Plastic spuit 1 ml	56A013501
Reageerbuis 5/10 mL + CAP	56A600401
Glycol-refractometer	56M000401

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Duitsland

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
Verenigd Koninkrijk

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Maleisië

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazilië

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Verenigde Staten

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spanje