

# Lovibond® Water Testing

## Tintometer® Group



## Disinfection Chlorine Test Kit

For monitoring of chlorinated water systems



Chlorination is the process of adding chlorine to water to prevent the spread of infection and disease (including Legionnaires' Disease).

Chlorinated water systems require careful monitoring to ensure the correct conditions are achieved and maintained during the chlorination process. Failure to achieve the correct chlorination levels can lead to unsuccessful disinfections while elevated levels can lead to potentially corrosive conditions.

This Disinfection Chlorine Test Kit has been designed to measure low and high levels of free chlorine. Test strips allow quick easy checking at Sentinel outlets.

- Maintenance before and after disinfection works
- Monitoring the correct chlorine concentration & avoiding damages
- Determination Chlorine, pH & more disinfection parameters
- Complete Kit for on-site testing

Artigo No: 56K701130

### Indústria

Outras Indústrias

### Aplicação

Água de Refrigeração | Controle de Desinfecção

### Disinfection Chlorine Test Kit

For commercial buildings, especially dormant premises, industry organisations recommend in many countries regular maintenance procedures for hot & cold-water services to prevent infection with bacteria, biofilms & material damage through misdosing.

The Lovibond® Disinfection Chlorine Test Kit assists you with testing instruments and reagents for monitoring the pH level, chlorine and other important parameters for safe water supply.

### Faixa de Medição

Test Name	Faixa de Medição
Cloro	10 - 200 mg/L Cl <sub>2</sub>
Cloro (livre)	1 - 300 mg/L Cl <sub>2</sub>
pH	7 - 14 pH

# Texto do Escopo de Entrega

- Plastic case
- pH strips, pH 7-14, plastic
- Chlorine HR strips, 10-200 mg/L
- Free Chlorine Buffer FCL1
- Free Chlorine LR Titrant FCL2
- Free Chlorine HR Titrant FCL3
- Syringe plastic, 20 mL
- Titration jar with cap, plastic, 60 mL
- Instruction manual

Título	Artigo No
Seringa, plástico, 20 mL	56A006501
Recipiente de titulação com tampa, plástico, 60 mL	56A006701

## Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Alemanha

## The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
Reino Unido

## Tintometer China

9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

## Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malásia

## Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brasil

## Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
EUA

## Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
Índia

## Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Espanha