

Copper T	M150
0.05 - 5 mg/L Cu ^{a)}	Cu
Biquinoline	

Instrument specific information

The test can be performed on the following devices. In addition, the required cuvette and the absorption range of the photometer are indicated.

Instrument Type	Cuvette	λ	Measuring Range
MD50, MD 100, MD 110, MD 200, MD 600, MD 610, MD 640, MultiDirect, PM 600, PM 620, PM 630, Test Kit	ø 24 mm	560 nm	0.05 - 5 mg/L Cu ^{a)}
SpectroDirect, XD 7000, XD 7500	ø 24 mm	559 nm	0.05 - 5 mg/L Cu ^{a)}

Material

Required material (partly optional):

Reagents	Packaging Unit	Part Number
Copper No. 1	Tablet / 100	513550BT
Copper No. 1	Tablet / 250	513551BT
Copper No. 2	Tablet / 100	513560BT
Copper No. 2	Tablet / 250	513561BT
Set Copper No. 1/No. 2 100 Pc.#	100 each	517691BT
Set Copper No. 1/No. 2 250 Pc.*	250 each	517692BT

Application List

- · Cooling Water
- · Boiler Water
- · Waste Water Treatment
- · Pool Water Control
- Drinking Water Treatment
- Galvanization



Preparation

 Strong alkaline or acidic water samples must be adjusted to pH 4 to 6 before analysis.



Determination of Copper, free with tablet

Select the method on the device.

In addition, choose the test: free


For this method, a ZERO measurement does not have to be carried out every time on the following devices: XD 7000, XD 7500



Fill 24 mm vial with 10 mL sample.




Close vial(s).



Place **sample vial** in the sample chamber. Pay attention to the positioning.





Press the **ZERO** button.

Remove the vial from the sample chamber.


For devices that require no ZERO measurement, start here.



Add COPPER No. 1 tablet



Crush tablet(s) by rotating slightly.




Close vial(s).





Dissolve tablet(s) by inverting.



Place **sample vial** in the sample chamber. Pay attention to the positioning.



Press the **TEST** (XD: **START**)button.



Wait for 2 minute(s) reaction time.

Once the reaction period is finished, the measurement takes place automatically. The result in mg/L free Copper appears on the display.



Determination of Copper, total with tablet

Select the method on the device.

In addition, choose the test: total


For this method, a ZERO measurement does not have to be carried out every time on the following devices: XD 7000, XD 7500



Fill 24 mm vial with **10 mL** sample.



Close vial(s)



Place **sample vial** in the sample chamber. Pay attention to the positioning.





Press the **ZERO** button.

Remove the vial from the sample chamber.

For devices that require no ZERO measurement, start here.



Add COPPER No. 1 tablet



Crush tablet(s) by rotating slightly and dissolve.



Add COPPER No. 2 tablet .






Crush tablet(s) by rotating slightly.



Close vial(s).




Dissolve tablet(s) by inverting.



Place **sample vial** in the sample chamber. Pay attention to the positioning.



Press the **TEST** (XD: **START**)button.



Wait for 2 minute(s) reaction time.

Once the reaction period is finished, the measurement takes place automatically.

The result in mg/L total Copper appears on the display.



Determination of Copper, differentiated determination with Tablet

Select the method on the device.

In addition, choose the test: differentiated


For this method, a ZERO measurement does not have to be carried out every time on the following devices: XD 7000, XD 7500



Fill 24 mm vial with 10 mL sample.




Close vial(s).



Place **sample vial** in the sample chamber. Pay attention to the positioning.





Press the **ZERO** button.

Remove the vial from the sample chamber.


For devices that require no ZERO measurement, start here.



Add COPPER No. 1 tablet



Crush tablet(s) by rotating slightly.




Close vial(s).






Dissolve tablet(s) by inverting.



Place **sample vial** in the sample chamber. Pay attention to the positioning.




Press the **TEST** (XD: **START**)button.



Wait for 2 minute(s) reaction time.



Remove the vial from the sample chamber.



Add COPPER No. 2 tablet .



Crush tablet(s) by rotating slightly.




Close vial(s).



Dissolve tablet(s) by inverting.





Place **sample vial** in the sample chamber. Pay attention to the positioning.

Test

Press the **TEST** (XD: **START**)button.



Wait for 1 minute(s) reaction time.

Once the reaction period is finished, the measurement takes place automatically.

The result in mg/L free Copper; combined Copper; total Copper appears on the display.



Chemical Method

Biquinoline

Appendix

Calibration function for 3rd-party photometers

Conc. = $a + b \cdot Abs + c \cdot Abs^2 + d \cdot Abs^3 + e \cdot Abs^4 + f \cdot Abs^5$

	ø 24 mm	□ 10 mm
а	-4.78562 • 10 ⁻²	-5.12445 • 10 ⁻²
b	3.79263 • 10 ⁺⁰	8.20998 • 10+0
С		
d		
е		-
f		

Interferences

Persistant Interferences

1. Cyanide CN⁻ and Silver Ag⁺ interfere with the test result.

Method Validation

Limit of Detection	0.05 mg/L
Limit of Quantification	0.15 mg/L
End of Measuring Range	5 mg/L
Sensitivity	3.8 mg/L / Abs
Confidence Intervall	0.026 mg/L
Standard Deviation	0.011 mg/L
Variation Coefficient	0.42 %

Bibliography

Photometrische Analyse, Lange/Vedjelek, Verlag Chemie 1980

^{a)} determination of free, combined and total | * including stirring rod, 10 cm